Data Sheet

HUBER+SUHNER

Coaxial Panel Connector 23_SMA-50-0-62/199_N

Description

Straight panel receptacle jack, flange mount

Interface standards IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	18 GHz	
Mechanical Data		
Number of matings	500	
Weight	0.0021 kg	
Environmental Data		
Operating temperature	-65 °C to 165 °C	
2011/65/EU (RoHS - including	compliant	
2015/863 and 2017/2102)		
Material Data		
Photo Proto	•• • • •	
Piece Parts	Material	Surface Plating
Centre contact	Material Copper Beryllium Alloy	Surface Plating Gold Plating (Nickel underplated)
		•
Centre contact	Copper Beryllium Alloy	•
Centre contact Outer contact	Copper Beryllium Alloy Stainless Steel	•
Centre contact Outer contact Body	Copper Beryllium Alloy Stainless Steel Stainless Steel	•
Centre contact Outer contact Body Insulator	Copper Beryllium Alloy Stainless Steel Stainless Steel	•
Centre contact Outer contact Body Insulator Related Documents	Copper Beryllium Alloy Stainless Steel Stainless Steel PFA / PTFE	•

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.