
1								53.0	00 ±0	0.38	
12.60 ±0.38	E0.25				•			47.0	04 ±0	0.25	
2.60	8.36 ±0.25	2.84				•		3	8.96	3	 1
_	w		,	_							
		- -	-	©	4	• •	•		• • •	• • •	
1	<u>'</u>							2.	77		
					ľ	1	+		 385		




UNLESS O	TOLERANCE UNLESS OTHERWISE SPECIFIED			
.X	±0.25			
XX	+0.13			


.XXX ±0.10

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL





NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, TIN PLATED

CONTACT: COPPER ALLOY, 30µ GOLD PLATED

OPERATING TEMPERATURE: -55°C to +85°C

CURRENT RATING: 3A PER CONTACT CONTACT RESISTANCE: 25mΩ MAX. INSULATOR RESISTANCE: 5000MΩ min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms

PART NUMBER:

627 SERIES D-SUB CONNECTOR



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

SW REFERENCE NO.: 627 ASSEMBLY									
DRAWN: C.B	DATE: AUG. 01/2018								
CHECKED:	DATE:								
SCALE: 1:1	SHEET 1 OF 1								
DRAWING NUMBER: 627-025-6	320-247 ISSUE								

627-025-620-247



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.