









NOTES: MATERIAL: HOUSING: THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED SHELL: CONTACT: COPPER ALLOY, GOLD FLASH PLATED 10.67 **OPERATING TEMPERATURE:** -55°C ~ 125°C 30A (CURRENT) POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX. Θ **INSULATOR RESISTANCE:** 5000MΩ min. DIELECTRIC Ø 0 0 WITHSTANDING VOLTAGE: 1000V AC rms 20.33

.XX ±0.13 .XXX ±0.05

			SW REFERENCE NO.: 629 COMBO ASSEMBLY			
			DRAWN: C.B	DATE: JAN. 01/201	19	
			CHECKED:	DATE:		
то	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
VES NCY.	YOUR CONNECTION TO QUALITY & SERVICE	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 629-25W	3250-3N6	ISSUE	
			PART NUMBER: 629-25W	3250-3N6	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVE 2011/65/EU FOR RoHS COMPLIANC

COMBINATION D-SUB			SW REFE	RENCE NO.:	629
			DRAWN:	C.B	
			CHECKED	D:	
	EDAC INC TORONTO, ONTARIO	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE:	(IN C.A.D. 1:1)	
		SHALL NOT BE REPRODUCED, OR COPIED			0_25\/

