

REVISIONS

APPR

TOMMY

TOMMY

BY

IAN

IAN

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK SEAL: SILICONE RUBBER

2. MODIFICATIONS: SMOOTH RING ADAPTER (SRA); REDUCED DIA. WIRE SEAL;

3. SPECIFICATIONS:


3.1 OPERATING TEMPERATURE:-55 °C TO +125°C. 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.

- 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
- 3.4 MOISTURE RESISTANCE: IP67&IP69K (MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP06-24-35P* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL WIRE	CURRENT
SIZE	O.D.	O.D.	RANGE	RATING
20	1.02 mm (.040 in)	2.41 mm (.095 in)	16-22 AWG (1.5-0.5mm²)	7.5 AMPS
16	1.35 mm (.053in)	3.05 mm (.120 in)	14-20 AWG (2.0-0.5mm²)	13 AMPS

7. RECEPTACLE IS SUPPLIED WITH DUST CAP.



RECOMMENDED PANEL MOUNTING HOLE

RECOMMENDED PANEL THICKNESS:1.6 TO 4.7MM

	XI.
SMOOTH RING ADAPTER - BLUE	AHUPU4-24-35SR-SRA

	AHDP04-2	4-35SR-SRA		REF:AHDP04-24-35SR-SRA				
	PART N	NUMBER			DESCRIPTION			ITEM
QUANTITY	MATERIALS LIST							•
UNLESS OTHER	WISE SPECIFIED	SIGN	NATURES	DATE		Λ	mphono	I
2) Tolerances are a		DRAWN:	IAN.XIAO	11AUG20			mpheno	ı
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:	ORION.LI	12AUG20	Sine Systems - www.amphenol-sine.com			
3) Note reference	= <u>x</u>	ENGINEER:			44724 Morley Drive			
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY.XIE	13AUG20	Clinton Township, MI 48036			
		CUSTOMER:		•			RECEPT,SIZE 24,35-SOCKET,	
			NG IS SUPPLIED N ONLY, DESIG					RES
PROCESS SPECIFICA	TIONS:	SPECIFICATION SHOWN HERE THE AMPHEN OF REPRODU	ONS AND PERF EON ARE THE F IOL CORPORAT JCTION ARE IMI	D PERFORMANCE DATA E THE PROPERTY OF PORATION. NO RIGHTS ARE IMPLIED. ALL BJECT TO NORMAL		C-	AHDP04-24-35SR-SR/	A A2
NEXT ASSY:			RING VARIATIO		SCALE: NONE DURAMATE SHEET 1 OF			or 1

ATM Series™ - Contact Size 20 Options

Machined Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Туре		
AT60-010-2031	Male Contact - Pin, Gold-plated	20	16-18	Machined		
AT62-005-20141	Female Contact - Socket, Gold-plated	20	16-18	Machined		
AT60-010-20141	Male Contact - Pin, Nickel-plated	20	16-18	Machined		
AT62-005-2031	Female Contact - Socket, Nickel-plated	20	16-18	Machined		
AT60-202-2031	Male Contact - Pin, Gold-plated	20	20-22	Machined		
AT62-201-2031	Female Contact - Socket, Gold-plated	20	20-22	Machined		
AT60-202-20141	Male Contact - Pin, Nickel-plated	20	20-22	Machined		
AT62-201-20141	Female Contact - Socket, Nickel-plated	20	20-22	Machined		

	Tooling - Machined Contacts					
Part	Part Number	Description				
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)				
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)				

Contact Removal Tools					
Part	Part Number	Description			
from hard	ATRT-100	Used for removal of contacts for A Series™ products			
	AT11-240-2005	Contact Removal Tool, Plastic, Size 20			
	AT13-204-2005	Sealing Plug, Size 20, White			

Stamped & Formed Contacts, Sockets & Pins							
Part Number	Description	Size	AWG	Туре			
AT60-20-0144	Male Contact - Pin, Gold-plated	20	16-22	Stamped & Formed			
AT62-20-0144	Female Contact - Socket, Gold-plated	20	16-22	Stamped & Formed			
AT60-20-0244	Male Contact - Socket, Gold-plated	20	16-22	Stamped & Formed			
AT62-20-0244	Female Contact - Socket, Gold-plated	20	16-22	Stamped & Formed			
AT60-20-0122	Male Contact - Pin, Nickel-plated	20	16-22	Stamped & Formed			
AT62-20-0122	Female Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed			
AT60-20-0222	Male Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed			
AT62-20-0222	Female Contact - Socket, Nickel-plated	20	16-22	Stamped & Formed			
AT60-20-0277	Male Contact - Socket, Tin-plated	20	16-22	Stamped & Formed			
AT62-20-0277	Female Contact - Socket, Tin-plated	20	16-22	Stamped & Formed			
AT60-20-0422	Male Contact - Socket, Nickel-plated	20	20-22	Stamped & Formed			
AT62-20-0444	Female Contact - Socket, Gold-plated	20	20-22	Stamped & Formed			

Tooling - Stamped & Formed Contacts						
Part	Part Number	Description				
	MFX-3974	Crimp Die - Size 20 (\$&F contacts only)				
	MFX-3976	Crimp Die - Size 20 (S&F contacts only) 20-22AWG -04XX Series				
No.	MFX-3978	Crimp Die - Size 20 (S&F contacts only) 20-22AWG -02XX Series				
	ATT-20-00	Hand Crimp Tool - Size 20, 20AWG (S&F contacts only)				

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

AT Series™ - Contact Size 16 Options

Machined Contacts, Sockets & Pins					
Part Number Description			AWG	Туре	
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined	
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined	
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined	
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined	
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined	
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined	
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined	
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined	
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined	
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined	
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined	
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined	

	Tooling - Machined Contacts					
Part	Part Number	Description				
	CA-5D12	Universal Hand Crimp Tool, Size 12/16/20 (Machined contacts only)				
3	CA-5E12	Pneumatic Crimp Tool, Size 12/16/20 (Machined contacts only)				

	Contact Removal Tools						
Part	Part Number	Description					
3	ATRT-100	Used for removal of contacts for A Series™ products					
	AT11-310-1605	Contact Removal Tool, Plastic, Size 16					
	A114017	Sealing Plug, Size 16, White					

Stamped & Formed Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Type		
AT60-14-0144	Male Contact - Pin, Gold-plated	16	14-16	Stamped & Formed		
AT62-14-0144	Female Contact - Socket, Gold-plated	16	14-16	Stamped & Formed		
AT60-14-0122	Male Contact - Pin, Nickel-plated	16	14-16	Stamped & Formed		
AT62-14-0122	Female Contact - Socket, Nickel-plated	16	14-16	Stamped & Formed		
AT60-16-0144	Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed		
AT62-16-0144	Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed		
AT60-16-0122	Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed		
AT62-16-0122	Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed		
AT60-16-0644	Male Contact - Pin, Gold-plated	16	18-20	Stamped & Formed		
AT62-16-0644	Female Contact - Socket, Gold-plated	16	18-20	Stamped & Formed		
AT60-16-0622	Male Contact - Pin, Nickel-plated	16	18-20	Stamped & Formed		
AT62-16-0622	Female Contact - Socket, Nickel-plated	16	18-20	Stamped & Formed		
AT60-16-0844	Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed		
AT62-16-0844	Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed		
AT60-16-0822	Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed		
AT62-16-0822	Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed		

Tooling - Stamped & Formed Contacts		
Part	Part Number	Description
	MFX-3950	Crimp Die - Size 16, 18-20AWG (S&F contacts only)
	MFX-3953	Crimp Die - Size 16, 16-18AWG (S&F contacts only)
	MFX-3975	Crimp Die - Size 16, 14-16AWG (S&F contacts only)
	MFX-3990	Crimp Die - Size 16, 20-22AWG (S&F contacts only)
	ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only)
	ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only)
	ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only)

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021