



MARKING:

(UL) E305668 TYPE CM 28AWG 75°C C(UL) E305668
 CM 28AWG 75°C ETL VERIFIED TIA/EIA-568.2-D
 MINI UTP CAT.6A RoHS COMPLIANCE BATCH NO.



P1	P2	
1	1	WHITE/ORANGE
2	2	ORANGE
3	3	WHITE/GREEN
6	6	GREEN
4	4	BLUE
5	5	WHITE/BLUE
7	7	WHITE/BROWN
8	8	BROWN

*NOTE: All relevant materials are complied with RoHS directive .
 THE LABEL IS WATERPROOF.

3	8P8C TRANSPARENT BOOT(OD4.5mm)	A4FK36-0205	2	M205
2	4 TWISD PAIRS MINI CAT.6A 28AWG UTP, OD 3.6mm, JACKET GREY-WHITE, DRAWING No.EU002804P-799	H5AJ61-0304G07	L+10mm	M304
1	8P8C MODULAR PLUG, GOLD PLATING 50u" ON CONTACTS, NO:P8-063-11	A1NC36-0205	2	M205
No.	DESCRIPTION		Q'TY	Supplier
APPROVED			Cable Length Unless Other Spec. Tolerances:	
CHECKED			0 ~200mm	±10mm
DRAWING			201~1000mm	±20mm
			1001 ~1500mm	±25mm
			1501~2100mm	±30mm
			2100mm↑	±40mm
DATE	15/JUL/19	ITEM NO.	CS6A-XXF-YYY	UNIT:mm

CHECKED

