



TABLE: *

ASSEMBLY	VIN+	U1	C8	C9	C18	C20, C21	D4	Q4	Q5	Q6	R4	R6	R8	R13	R17	R18	R20	R24	R26	T1
DC950A-A	36V-72V	LT3825EFE	12uF	150pF	22uF	2.2uF	OPT.	OPT.	Si4840DY	Si4488DY	OPT.	47K	91	402K	0.025	opt.	14.7K	12.4K	1.00K	PA2046NL
DC950A-B	9V-36V	LT3837EFE	47uF	560pF	OPT.	4.7uF	BZX84C11-V	MMBT3904LT	HAT2165H	Si7852DP	4.7K	OPT.	22.1	121K	0.015	0.015	22.1K	13.0K	750	PA2047NL

LTC CONFIDENTIAL - FOR CUSTOMER USE ONLY

Customer Notice
 Linear Technology Has Made A Best Effort To Design A Circuit That Meets Customer-Supplied Specifications; However, It Remains The Customer's Responsibility To Verify Proper And Reliable Operation In The Actual Application. Component Substitution And Printed Circuit Board Layout May Significantly Affect Circuit Performance Or Reliability. Contact Linear Technology Applications Engineering For Assistance.
 This Circuit Is Proprietary To Linear Technology And Supplied For Use With Linear Technology Parts.

LINEAR TECHNOLOGY CORPORATION
 1630 McCARTHY BLVD.
 MILPITAS, CA. 95035
 408-432-1900
 408-434-0507 FAX

Title: **Multi-Output Flyback in 1/8 Brick Format**

Size	Document Number	Rev
	Demo Circuit 950A-A/B LT3825EFE/LT3837EFE	A

Date: Thursday, October 11, 2007 Sheet 1 of 1