ABSOCIATION CONNECTING ELECTRONICS INDUSTRIES® International and Pa	PC, Bannock	burn, Illinois. A	All rights reserved untions.	under both	This docume level parts, t	ent is a declar the declaration	ration of n encom	f the substance passes all low	es within t ver level n	he manufactu naterials for v	urer listed it which the m	em. No anufact	te: if the iter turer has eng	m is an ass gineering r	embly with low esponsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					rials and Mi	ials and Mfg Information				
Supplier Information																
Company name* Compan			ompany unique ID			Unique ID Authority					Respons	Response Date*				
onsemi										2023-06-08						
Contact Name	ct I			Phone - Contact*					Email -	Email - Contact*						
Product-Env-Stewards P			Product Enviro Compliance			NA					Product	Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative			Phone - Representative*				Email - I	Email - Representative*					
Product-Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com							
Requester Item Number	Requester Item Number Mfr Iten		n Number Mfr Item Name			Effective Date Version Manufacturing Si		turing Site	V	Veight*	* UC	OM	Unit Type			
	MC74H	MC74HC11ADTG DUAL J-K F		FLIP FLOP		2023-06-08			PH1		4	45.24		ţ	Each	
Aanufacturing Proccess Informa	tion										L. L					
Terminal Plating / Grid Array M	aterial	1 Terminal Base Alloy		J-STD-020 MS	L Rating	Peak Process Bo		ody Temperature Max Time at Peak		k Temperat	Temperature Number of R		eflow Cycl	es		
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		CU Alloy 1		1		260		С	30		secon	seconds 3				
comments																
vel 1 - maximum time at peak temperat	ure during so	oldering is 10-3	0 seconds													
or more information regarding material	composition	please refer to	page 3													

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

				[e] • Freedom ( ) • • • • • • • • • • • • • • • • • •				
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.0	mg	Supplier	Silicon (Si)	7440-21-3		2	mg
Die Attach	1.44	mg	Supplier	Silver (Ag)	7440-22-4		1.08	mg
			Supplier	Epoxy resins	129915-35-1		0.36	mg
Lead Frame	22.54	mg	Supplier	Iron (Fe)	7439-89-6		0.4283	mg
			Supplier	Copper (Cu)	7440-50-8		22.1117	mg
Mold Compound-Black	19.0	mg		Epoxy resin	proprietary data		0.95	mg
			Supplier	Phenolic Resin	Proprietary Data		0.95	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.38	mg
			Supplier	Carbon Black (C)	1333-86-4		0.095	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		16.625	mg
Plating	0.04	mg	Supplier	Palladium (Pd)	7440-05-3		0.003	mg
			В	Nickel (Ni)	7440-02-0		0.0364	mg
			Supplier	Gold (Au)	7440-57-5		0.0006	mg
Wire Bond - Cu	0.22	mg	Supplier	Copper (Cu)	7440-50-8		0.22	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).