

Universal Reversible USB 2.0 Cable (Reversible A to 5Pin Micro B M/M), 6-in.

MODEL NUMBER: UR050-06N



Universal / Reversible "A" connector allows plugging in any direction

Description

Tripp Lite UR050-06N, 6-in. USB 2.0 A to Micro-B cable, features a Universal / Reversible "A" connector, which takes the guesswork out of which way to position the "A" connector for plugging. Micro-USB is the next generation of USB connector that will be found on Cell Phones, PDA's, USB On-the-Go (OTG) devices, Digital Cameras, and more. Smaller and more durable (10,000 insertion cycles) than the existing mini-B connectors, the Micro-USB will also handle Power transfers, as well as Data. The USB Implementers Forum (USB-IF) has designed the Micro-USB to eliminate many of the proprietary Mini connectors found on different manufacturers digital devices, and it will be the standard USB connection on phones from the major cell phone manufacturers. USB 2.0 rated cable handles 480Mbps data transfer rates.

Features

- USB Universal / Reversible A Male to Micro-B Male
- Available in lengths up to 10 ft.
- 480Mbps USB 2.0 Data Transfer Rates
- Data and Power transference

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332182302 |
| INPUT | |

Highlights

- Next Generation USB Digital
 Device Connector
- Provides both Data and Power transfers
- USB 2.0 480Mbps Transfer rates
- Universal / Reversible "A" Male to Micro-B Male

System Requirements

Digital devices that use the USB
 Micro-B Female socket

Package Includes

6-in. USB2.0 Universal /
 Reversible A to Micro-USB B
 Device Cable (A Male to Micro-B Male)





| Cable Length (ft.) | 0.5 | |
|---|---------------------------|--|
| Cable Length (m) | 0.2 | |
| Cable Length (in.) | 6 | |
| Cable Length (cm) | 15.24 | |
| PHYSICAL | | |
| Color | Black | |
| Shipping Dimensions (hwd / cm) | 0.64 x 0.64 x 15.24 | |
| Shipping Dimensions (hwd / in.) | 0.25 x 0.25 x 6.00 | |
| Shipping Weight (kg) | 0.05 | |
| Shipping Weight (lbs.) | 0.10 | |
| Wire Gauge (AWG) | 28/28 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -10/+75° C (14 to 167° F) | |
| Storage Elevation (ft.) | -20/+80° C (-4 to 176° F) | |
| Storage Elevation (m) | -20/+80° C | |
| CONNECTIONS | | |
| Side A - Connector 1 | REVERSIBLE USB A (MALE) | |
| Side B - Connector 1 | MICRO-USB B (MALE) | |
| FEATURES & SPECIFICATIONS | | |
| Technology | USB 2.0 (High Speed); USB | |
| WARRANTY | | |
| Product Warranty Period | Lifetime limited warranty | |
| Operating Temperature Range -10/+75° C (14 to 167° F) Storage Elevation (ft.) -20/+80° C (-4 to 176° F) Storage Elevation (m) -20/+80° C CONNECTIONS Side A - Connector 1 REVERSIBLE USB A (MALE) Side B - Connector 1 MICRO-USB B (MALE) FEATURES & SPECIFICATIONS Technology USB 2.0 (High Speed); USB | | |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies