



114030K21MXXXG

Cable type  
14/4 AWG  
black TPE

Finished Length  
M005 = .5 Meters  
M010 = 1 Meter

**MECHANICAL**  
CONTACT : GOLD/NICKEL OVER COPPER ALLOY  
INSERT : BLACK PVC  
COUPLING NUT: ZINC DIE CAST, BLACK E-COAT  
MOLDED BODY: BLACK PVC  
CABLE: 14 AWG 4 CONDUCTORS BLACK TPE JACKET  
CABLE MARKING: [MFG. UL FILE NO.] 14 AWG (2.08mm<sup>2</sup>)  
UL TYPE TC-ER/MTW (UL) THHN/THWN  
600V 90C DRY 75C WET OIL RES SUN  
RES [MFG. CSA FILE NO.] CSA AWM  
I/II A/B 105C W75 1000V -40C FT4

**ELECTRICAL**  
VOLTAGE RATING: 600V AC/DC  
AMPERAGE: 15A

**ENVIRONMENTAL**  
PROTECTION: IP67

UPDATED DRAWING EC NO: IPG2016-1628 DRWN: GGUSTAFS 2016/06/02 CHKD: MZIELINS 2016/06/15 APPR: BWOODMAN 2015/11/09	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH/MM		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION
		▽=0	mm	INCH	DRAWN BY	DATE	TITLE	Molex	SHEET NO.
		∇=0	4 PLACES ±---	±---	KCOX01	2015/10/19			
			3 PLACES ±---	±---	CHECKED BY	DATE			
			2 PLACES ±---	±---	BARDEN	2015/10/19	SD-130062-023	1 OF 1	
	1 PLACE ±---	±---	APPROVED BY	DATE					
	ANGULAR ±---°	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE MATRIX		DOCUMENT NO.			
				SIZE B		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			