

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.










NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED

THERMOPLASTIC POLYESTER, UL94V-0



POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

.X ±0.25 .XX ±0.13 .XXX ±0.05

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE:


**OPERATING TEMPERATURE:** 

10A (CURRENT)

-55°C ~ 125°C

5000MΩ min.

1000V AC rms



|      | COMBINATION D-SUB                    |   | SW REFERENCE NO.: 629 COMBO ASSEMBLY |                  |       |
|------|--------------------------------------|---|--------------------------------------|------------------|-------|
|      |                                      |   | DRAWN: C.B                           | DATE: JAN. 01/20 | 19    |
|      |                                      |   | CHECKED:                             | DATE:            |       |
|      | EDAC INC                             | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INCAND  | SCALE: (IN C.A.D. 1:1)               | SHEET 1 OF       | 2     |
| YOUR | YOUR CONNECTION TO QUALITY & SERVICE | SHALL NOT BE REPRODUCED, OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 629-9W4-250-1TC      |                  | ISSUE |
|      |                                      |   | PART NUMBER: 629-9W4-                | -250-1TC         | 1     |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

