



.XX ±0.13


.XXX ±0.05





(1)






## NOTES:

MATERIAL:<br/>HOUSING:THERMOPLASTIC POLYESTER, UL94V-0<br/>STEEL, TIN PLATED<br/>COPPER ALLOY, 30μ GOLD PLATEDOPERATING TEMPERATURE:-55°C ~ 125°CPOWER/CO-AX CONTACT RATING:75Ω (IMPEDANCE)


(IF PRESENT)SIGNAL CONTACT CURRENT RATING: 5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:





	COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY		
			DRAWN: C.B	DATE: JAN. 01/20	19
			CHECKED:	DATE:	
YOUR CONNECTION	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
	TORONTO, ONTARIO CANADA		DRAWING NUMBER: 630-17W2640-7TE		ISSUE
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-17W	2640-7TE	1





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

