

Connector Component			Connector Strip Dimension			Wire Spec.	Terminal ROJ & Strip		
Color	Component	Qty	Strip	ROJ	Color		Strip	ROJ	Color
40P BK 90±5 °A	IEC 320 C13 (LT-511R(10A 250V))	1	7±1	20±3	Black	SVT 18AWGX3C 105°C BLACK  Length: 500±10 mm	$\frac{5}{8}$ " (16mm)	2" (50.8mm)	Black
Copper	computer power cord terminals	3	7±1	20±3	White		$\frac{5}{8}$ " (16mm)	2" (50.8mm)	White
White	(511 Inner Body)	1	7±1	20±3	Green		$\frac{5}{8}$ " (16mm)	2" (50.8mm)	Green

**NOTE :**



1. PLUG : NA
2. CONNECTOR : LT-511R IEC-60320 C13
3. CORD : SVT 18AWGX3C 105°C BLACK 0.5M
4. APPROVALS : UL, C-UL
5. Supplier for flexible cord : I-SHENG
6. Hi-Pot Test:2000v/1min<1mA>

**Marking:**

I-SHENG:(UL)E88265 SVT SHIELED 105°C 3X18AWG(0.824mm<sup>2</sup>)  
300V VW-1 I-SHENG CSA LL81924 TYPE SVT SHIELED  
105°C 3X0.824mm<sup>2</sup>(18AWG) 300V VW-1

**Modification History**

NO.	DESCRIPTION	DATE

<b>DRAWER</b>	Aaron	<b>DATE</b>	20/11/05	<b>P/N</b>	800-1803-2-SVT0-BL-00050-2
<b>APPROVE</b>		<b>REV.</b>	0	<b>Dr.No.</b>	1091111
		比例		<b>TOL.</b>	±5mm
				<b>ALL DIMENSIONS IN mm</b>	

**CnC Tech**  
Industrial Cable and Connector Technology