

Page 1 of 6

SAFETY DATA SHEET SDS-E-GX5S Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision Date: 5/15/2020 SDS Revision: 6.3 1. PRODUCT & COMPANY IDENTIFICATION 1 1 Product Name DEOXIT® GOLD Gx-SERIES GX5, 5% SPRAY, NON-FLAMMABLE, VOC COMPLIANT 1.2 Chemical Name: 1.3 Synonyms DeoxIT® Gold Gx-Series 5% Spray; GX5S-6N and GX5S-2N (mini-spray) 1.4 Trade Names: DeoxIT® Gold Gx-Series 5% Spray; PN GX5S-6N (163 grams), PN GX5S-2N (40 grams) 1.5 Product Use: Conditioner, enhancer for plated and gold plated electronic contacts & connectors 1.6 Distributor's Name: CAIG Laboratories, Inc. 1.7 Distributor's Address: 12200 Thatcher Court, Poway, CA 92064-6876 USA 1.8 Emergency Phone: CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN205206) 1.9 Business Phone / Fax: +1 (800) 224-4123 2. HAZARDS IDENTIFICATION This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification 2 1 Hazard Identification: criteria of NOHSC: 1088 (2004) and ADG Code (Australia). WARNING! PRESSURIZED CONTAINER; MAY BURST IF HEATED. CAUSES EYE IRRITATION. Classification: Aerosols 3, Eye Irrit. 2B 2.2 Label Elements: Hazard Statements (H): H229 - Pressurized container; may burst if heated. H320 - Causes eye Precautionary Statements (P): P210 - Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. P251 - Do not pierce or burn, even after use. P264 - Wash thoroughly after handling. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy. Continue rinsing. P337+P313 - If eye irritation persist: Get medical advice/attention. P403 – Store in a well-ventilated place. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF) Other Warnings: KEEP OUT OF REACH OF CHILDREN. 3. COMPOSITION & INGREDIENT INFORMATION EXPOSURE LIMITS IN AIR (mg/m³) **ACGIH** NOHSC **OSHA** ppm ppm ppm ES-ES-ES-RTECS No. STFI CHEMICAL NAME(S) CAS No. **EINECS No.** TI V STEL TWA STEL **PEAK** PFI IDI H OTHER 102687-65-0 NA NA 60-100 NA NA NF NF NF NA NA NA SOLSTICE® PF REACH Reg. No. 01-2119855084-38 1-PROPENE, 1,3,3,3-29118-24-9 NA NA 15-30 NA NA NF NF NA NA NA NF TETRAFLUORO-, (1E) REACH Reg. No. 01-0000019758-54 NA NA NF NF NF 15 NA DEOXIT ® GOLD GX100L NA NA NA 3-7 NA (TRADE SECRET) REACH Reg. No. Non-hazardous/Proprietary 4. FIRST AID MEASURES If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk First Aid Ingestion: IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed Splashes are not likely; however, mist may cause irritation. If product gets in the eyes may cause irritation; Eyes: flush with copious amounts of lukewarm water for at least 15 minutes lifting upper and lower lids, occasionally. If irritation persists repeat flushing. Get medical attention. Skin: Wash thoroughly with soap and water. In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Treat for frostbite if necessary, be gently warming affected area. If irritation, redness or swelling persists, contact a physician immediately. Remove victim to fresh air at once. If breathing difficult, administer oxygen. Gross overexposure may Inhalation: cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping," apprehension, lightheadedness, weakness, fainting, loss of consciousness, and death. 42 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea. Ingestion: Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and Eyes: watering. May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in Skin: some sensitive individuals.

> Gross overexposure may cause central nervous system depression, dizziness, confusion, incoordination, drowsiness, irregular heartbeat accompanied by a strange feeling in the chest, "heart thumping,"

apprehension, light-headedness, weakness, fainting, loss of consciousness, and death.

Inhalation:



Page 2 of 6 SDS-E-GX5S

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 6.3 SDS Revision Date: 5/15/2020

3	Symptoms of Overexposure:	Ingestion:	Nausea, intestin	al discomfort	, vomitin	g and/or di	iarrhea.						
		Eyes:	Overexposure in			•		atering.					
		Skin:	Symptoms of sk										
			like symptoms.	The produc	ct can ca	ause allerg	ic skin r	eactions (e.g., rasł	hes, welt	s, derm	atitis) in	102
		Inhalation	individuals. Gross overexpo	may aa	uaa aant	ral namen	a avatam	donrocci	on diaain		fusion	inacardir	natio
		Inhalation:	drowsiness, irre	egular heartl	beat acc	companied	bv a s	strange fe	elina in	the che	est. "he	art thum	npin
			apprehension, li										
4	Acute Health Effects:		ritation to eyes a						h concen	ntrations	of vapo	ors can	cau
5	Chronic Health Effects:		dizziness, headac						N4	- Sections	-1-1		
J	Chiloriic Fleatti Effects.		re may trigger ast hypersensitivity. Po				nsitive in	aividuais.	way als	io induce	SKIN SE	ensilizatio	on a
6	Target Organs:		Respiratory Syster										
7	Medical Conditions		dermatitis, other			disorders	of the	HEALT	Н			1	1
	Aggravated by Exposure:	target organ	s (eyes, skin, and	respiratory s	ystem).			FLAMM	IABILIT'	Υ		1	1
								PHYSIC					0
								PROTE			IENT		Š B
							ŀ	EYES	SKIN				
							I		0.1	• .			
			5. FIR	EFIGHT	ING N	/IEASU	RES						
1	Fire & Explosion Hazards:	Level 1 Aero	osol (NFPA 30B).					ve 120 °F	. Cool u	ninvolved	d		
		containers to	o prèvent possible	e bursting.	Áerosols	may be	projectile	hazards	when bu	rsting. I	lf		
			e bursting, stay o										
			involved in a fire CO, Hydrogen Flu		ct may d	iecompose	at high	temperat	ures to t	orm toxic	С		
2	Extinguishing Methods:		n, CO ₂ , Dry Chemi		ter snrav	to cool un	onened o	ontainers				1	
		Water, I dan			toi opiay	to cool un							
	Firefighting Procedures:	5.3 Firefighting Procedures: Fight fires as for surrounding materials. As in any fire, wear MSHA/NIOSH approved self-						- /		$\mathbf{\alpha}$			
	Firefighting Procedures:		as for surroundin	g materials.	As in	any fire,						1	0
	Firefighting Procedures:	contained br		g materials. s (pressure-d	As in lemand)	any fire, and full pr	otective (gear. Ke	ep contai	iners coo	ol		0
	Firefighting Procedures:	contained br until well af personal. F	as for surroundin reathing apparatus ter the fire is ou -ight fire upwind.	g materials. (pressure-d t. Use wate Avoid spra	As in lemand) er spray ying wat	any fire, and full pr to cool fi er directly	otective (re-expos into sto	gear. Ke ed surfac rage conta	ep contai es and t ainers be	iners coo to protec ecause o	ol et of		0
	Firefighting Procedures:	contained br until well af personal. F danger of b	as for surroundin reathing apparatus fer the fire is ou Fight fire upwind. poil-over. Prevent	g materials. s (pressure-d t. Use wate Avoid spra t runoff from	As in lemand) er spray ying wat	any fire, and full pr to cool fi er directly ntrol or di	otective of re-expos into sto lution fro	gear. Ke ed surfac rage conta m enterin	ep contai es and t ainers be ng sewers	iners coo to protec ecause o s, drains	ol et of s,		0
	Firefighting Procedures:	contained br until well af personal. F danger of b drinking wat	as for surroundin reathing apparatus fter the fire is ou Fight fire upwind. soil-over. Prevent fer supply, or any	g materials. c (pressure-d t. Use wate Avoid spra t runoff from natural wate	As in lemand) er spray ying wat n fire colerway.	any fire, and full pr to cool fi er directly ntrol or di Firefighters	otective (re-expos into sto lution fro must us	gear. Ke ed surfac rage cont m enterin e full bun	ep contai es and t ainers be ng sewers ker gear	iners coo to protec ecause o s, drains including	ol et of s,		0
	Firefighting Procedures:	contained br until well af personal. F danger of b drinking wat NIOSH-appr	as for surroundin reathing apparatus fer the fire is ou Fight fire upwind. poil-over. Prevent	g materials. c (pressure-d t. Use wate Avoid spra t runoff from natural wate ssure self-co	As in lemand) er spray ying wat n fire colerway. Fintained lemander in the second seco	any fire, and full property to cool fixer directly introl or distinction of the control of the c	otective of re-expose into sto lution from must us apparatus	gear. Ke ed surfac rage conta m enterin e full bun s to protec	ep contai es and t ainers be ng sewers ker gear	iners coo to protec ecause o s, drains including	ol et of s,	1	0
	Firefighting Procedures:	contained br until well af personal. F danger of b drinking wat NIOSH-appr	as for surrounding apparatuse the fire is our sight fire upwind. soil-over. Preventier supply, or any soved positive presombustion or decompusion or decompusion or decompusitive presombustion or decompusitive presonance present the	g materials. c (pressure-d t. Use wate Avoid spra t runoff from natural wate ssure self-co	As in lemand) er spray ying wat in fire concerway. For the interest in force the interest in t	any fire, and full pr to cool fi er directly ntrol or di Firefighters breathing a and oxygen	otective of re-expose into sto lution from must us apparatus deficience	gear. Keed surface rage contains entering to the full bunks to protecties.	ep contai es and t ainers be ng sewers ker gear	iners coo to protec ecause o s, drains including	ol et of s,		0
3		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c	as for surrounding apparatus fer the fire is our light fire upwind. soil-over. Preventer supply, or any loved positive presombustion or deco	g materials. s (pressure-d t. Use wate Avoid spra t runoff from natural wate ssure self-co emposition pr	As in lemand) er spray ying wat in fire colerway. For the roducts a	any fire, and full pr to cool fi er directly ntrol or di Firefighters breathing a and oxygen	otective of re-expose into sto lution from must us apparatus of deficience.	gear. Ke ed surfac rage conta m enterin e full bun s to protec cies.	ep contai es and t ainers be ng sewers ker gear ct against	iners coo to protec ecause o s, drains includino t potentia	ol et of s, g		0
	Firefighting Procedures: Spills:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c	as for surrounding apparatus fer the fire is our fight fire upwind. Soil-over. Preventier supply, or any coved positive presombustion or decomposition or decomposition any spill or	g materials. s (pressure-d t. Use wate Avoid spra t runoff from natural wate ssure self-co emposition pr	As in demand) er spray ying wat in fire colerway. Findained broducts a telephone to the colerway of the colerw	any fire, and full pr to cool fiver directly ntrol or di Firefighters breathing and oxygen	re-exposinto sto lution fromust us apparatus deficient	gear. Keed surface rage contains entering full bun to protecties. RES nup must	ep contai es and t ainers be ng sewers ker gear ct against	iners coo to protec ecause o s, drains including t potentia	e Perso		
3		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment.	as for surrounding apparatus for the fire is our light fire upwind. Soil-over. Preventer supply, or any loved positive presombustion or decompositive pression and spill or Plastic or rubber	g materials. c (pressure-d t. Use wate Avoid spra t runoff from natural wate ssure self-co emposition pr NTAL R leak, indivic gloves, resp	As in lemand) er spray ying wat in fire colerway. For intained is coducts a lemant in the lemant in	any fire, and full protocool fiver directly ntrol or discretishers breathing a and oxygen as EME we protectic	otective of re-exposed into sto lution from must us apparatus of deficient deficient deficient control and apparant apparatus on and apparatus on a control apparatus on a contr	gear. Keed surface rage contains entering to protections. RES nup must ron may be	ep contai es and t ainers be ng sewers ker gear et against wear ap be require	iners coo to protec ecause o s, drains including t potentia	e Perso	large sp	oills.
3		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills	as for surrounding apparatus fer the fire is our light fire upwind. It is solid to the fire is our light fire upwind. It is solid to the fire is our light fire upwind. It is solid to the fire is sol	g materials. g (pressure-d t. Use wate Avoid spra t runoff from natural wate ssure self-co emposition pr NTAL R leak, indivic gloves, respe e protective	As in lemand) er spray ying wat in fire concerway. Fintained broducts a ELEA duals invirator, ey equipme	any fire, and full pr to cool fiver directly ntrol or di Firefighters preathing a and oxygen SE ME rolved in sere protectiont includin	re-expose into sto lution from must us apparatus deficience. EASUI spill clear and app g gloves	gear. Keed surface rage contains entering to protections. RES nup must ron may be and protections.	ep contai es and t ainers be ng sewers ker gear et against wear ap be require ective eye	iners coo to protec ecause o s, drains including t potentia ppropriate ed for clea	e Perso	f large sp on-combเ	oills. ustik
3		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc	as for surrounding apparatus for the fire is our light fire upwind. Soil-over. Preventer supply, or any loved positive presombustion or decompositive pression and spill or Plastic or rubber	g materials. g (pressure-d t. Use wate Avoid spra t runoff from natural wate ssure self-co emposition pr NTAL R leak, indivic gloves, resp e protective or sand to so	As in lemand) er spray ying wat in fire concerway. Fintained to coducts a duals invitator, ey equipme bak up the	any fire, and full protocool fiver directly introl or discretified and oxygen as the protocool of the protocool of the product and full produc	otective of re-expose into sto lution from must us apparatus deficience. EASUF spill clean and ap g gloves and place and plac	gear. Keed surfacerage contains entering to protections. RES nup must and protection may be and protection and protection and protection and protection and protection may be and protection and protection may be and protection and	ep contai es and t ainers be ag sewers ker gear et against wear ap be require ective eye container	iners coo to protec ecause o s, drains including t potentia oppropriate ed for clea	e Perso an-up of disposa	f large sp on-combเ al. Do no	oills. ustik ot u
3		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic brooi	as for surrounding apparatus for the fire is our light fire upwind. For supply, or any light of the supply, or any light of the supply, or any light of the supply over positive presombustion or decomposition or decomposition or decomposition or plastic or rubber is wear appropriate that as vermiculities and the supplementation of the suppleme	g materials. g (pressure-d t. Use wate Avoid spra t runoff from natural wate ssure self-co emposition pr NTAL R leak, indivic gloves, resp e protective or sand to so speedy dry" eans) and pla	As in lemand) er spray ying wat in fire concerway. Fintained to coducts a duals invitator, ey equipme bak up the to soak ice into a	any fire, and full proceed to cool fiver directly introl or differential formation of the cool of the	otective of re-expose into sto lution from must us apparatus deficience. EASUR spill clean and ap g gloves and place and pla	gear. Keed surface rage contains entering to protections. RES nup must and protection may be and protection and protection pup mater plastic limits and protection may be a prot	ep contai es and t ainers be ag sewers ker gear et against wear ap be require ective eye container erial using mer within	iners coo to protect ecause o s, drains including t potentia oppropriate ed for clea ewear. U for later g non-sp another	e Perso an-up of disposa arking r	f large sp on-combu al. Do no materials er.	oills. ustik ot u s (e.
3		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic brook Large Spills	as for surrounding apparatus for the fire is our cight fire upwind. It is not consider the fire is our cight fire upwind. It is not consider supply, or any coved positive presombustion or decombustion or plastic or rubber: Wear appropriate that we are the combustion of the co	g materials. c (pressure-d t. Use wate Avoid spra t runoff from natural wate ssure self-co pmposition pr NTAL R leak, indivic gloves, resp e protective or sand to so speedy dry" ans) and pla ble materials	As in lemand) er spray ying wath fire colorway. For the conducts a ELEA duals invitator, ey equipme bak up the to soak up to to soak up to soak	any fire, and full proceeding to cool five to cool five the cool five the cool five the cool for	otective of re-expose into sto lution from the must us apparatus of deficient expose into store the must us apparatus of deficient expose in and apparatus of the must be and apparatus of the must be and place all. Sweeth tainer out the must be a soil)	gear. Keed surface rage contains entering the full bunks to protections. RES The must represent the full bunks to protection the full bunks to protection the full bunks to protect the full bunks the full bunks to protect the full bunks the full bunks to protect the full bunks the full bunks the full b	ep contai es and t ainers be ig sewers ker gear ct against wear ap ective eye container erial using ner within n spill. S	iners coo to protec ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another etay upwii	e Personal P	f large spon-combual. Do no materials er. away fron	oills. ustik ot u (e.
3		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release.	as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind for any spill or light fire upwind	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water sure self-co pmposition pr NTAL R leak, indivice gloves, respe protective so presend to so present to s	As in lemand) er spray ying wath fire colorway. Fintained the roducts a ELEA duals invitation, eyequipme bath to soak up the colorway in the c	any fire, and full proceeding to cool five to cool five the cool five the cool five the cool for	re-exposinto sto into into sto into sto into into sto into sto into sto into sto into sto into sto into into sto into st	gear. Keed surface rage contains entering the full bunks to protections. RES The must represent the full bunks to protection the full bunks to protection the full bunks to protect the full bunks the full bunks to protect the full bunks the full bunks to protect the full bunks to protect the full bunks	ep contai es and t ainers be ag sewers ker gear et against wear ap be require ective eye container cerial using her within n spill. S of area.	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwin	e Perso an-up of disposa arking r containe nd and all or rele	f large spon-combulated. Do not materials er. away from ease if it o	oills. ustib ot u s (e.s om s can
3		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release.	as for surrounding apparatus for the fire is our cight fire upwind. It is not consider the fire is our cight fire upwind. It is not consider supply, or any coved positive presombustion or decombustion or plastic or rubber: Wear appropriate that we are the combustion of the co	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water sure self-co pmposition pr NTAL R leak, indivice gloves, respe protective so presend to so present to s	As in lemand) er spray ying wath fire colorway. Fintained the roducts a ELEA duals invitation, eyequipme bath to soak up the colorway in the c	any fire, and full proceeding to cool five to cool five the cool five the cool five the cool for	re-exposinto sto into into sto into sto into into sto into sto into sto into sto into sto into sto into into sto into st	gear. Keed surface rage contains entering the full bunks to protections. RES The must represent the full bunks to protection the full bunks to protection the full bunks to protect the full bunks the full bunks to protect the full bunks the full bunks to protect the full bunks to protect the full bunks	ep contai es and t ainers be ag sewers ker gear et against wear ap be require ective eye container cerial using her within n spill. S of area.	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwin	e Perso an-up of disposa arking r containe nd and all or rele	f large spon-combulated. Do not materials er. away from ease if it o	oills. ustib ot u s (e.s om s can
3		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release. done with m	as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind for any spill or light fire upwind	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water sure self-co pmposition pr NTAL R leak, indivice gloves, respe protective so presend to so present to s	As in lemand) er spray ying wat a fire colorway. For the colorway of the color	any fire, and full proceeding to cool five to cool five the cool five the cool five the cool for	re-exposinto sto into into into into into into into in	gear. Keed surface rage contains entering the full bunks to protections. RES The must represent the full bunks to protection the full bunks to protection the full bunks to protect the full bunks the full bunks to protect the full bunks the full bunks to protect the full bunks to protect the full bunks the full bun	ep contai es and t ainers be ag sewers ker gear et against wear ap be require ective eye container cerial using her within n spill. S of area.	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwin	e Perso an-up of disposa arking r containe nd and all or rele	f large spon-combulated. Do not materials er. away from ease if it o	oills. ustib ot u s (e.s om s can
3		contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release, done with m 7 Do not eat,	as for surrounding apparatus fer the fire is our light fire upwind. It is not light fire upwind for example of the second of	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water ssure self-co pmposition pr NTAL R leak, indivict gloves, resp pe protective or sand to so speedy dry" ans) and pla ple materials hazard area appropriate G & STC when handlir	As in lemand) er spray ying wath fire colorway. For the colorway of the colorw	any fire, and full proceeding to cool five to cool five to cool five the cool five protection of the cool for	re-exposinto sto lution from the store of th	gear. Keed surface rage contains entering the full bunks to protections. RES In the full bunks to protection may be and protection and protection and protection and protection away from sonnel outing respirate TION Under pre	ep contai es and t ainers be ig sewers ker gear ct against wear ap be require ective eye container erial using ner within n spill. S of area. tory prote	iners coo to protec ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwir Stop spi ection as	e Perso an-up of Jse a no disposa arking r containe nd and all or rele condition	f large spon-combual. Do no materials er. away froi ease if it coms warra	oills. ustib ot u i (e. om s can ant.
1	Spills:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous contained to the second	as for surrounding apparatus fer the fire is our light fire upwind. It is not light fire upwind for example of the second of	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water ssure self-co pmposition pr NTAL R leak, indivict gloves, resp pe protective or sand to so speedy dry" ans) and plater ble materials hazard area appropriate G & STC when handlir intended, no	As in lemand) er spray ying wath fire colorway. For the colorway of the colorw	any fire, and full protocool five to cool five to cool five to cool five the cool five protocool for the cool five protocool five protocool five protocool five protocool five equipments such that the cool five protocool five equipments such that the cool five the cool	re-exposinto sto lution from the store of th	gear. Keed surface rage contains entering the full bunds to protections. RES In the full bunds to protection may be and protection and protection and protection away from away from sonnel outing respiration. TION under prement is near the surface of the full bunder prement is near the surface of the full bunder prement is near the surface of the full bunder prement is near the surface of the full bunder prement is near the surface of the full bunder prement is near the full bunder prement in	ep contai es and t ainers be ig sewers ker gear ct against wear ap be require ective eye container erial using ner within n spill. S of area. tory prote	iners coo to protec ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwir Stop spi ection as	e Perso an-up of Jse a no disposa arking r containe nd and all or rele condition	f large spon-combual. Do no materials er. away froi ease if it coms warra	oills. ustib ot u i (e. om s can ant.
1	Spills: Work & Hygiene Practices:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous contained to the personal of the personal	as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind for any spill or plastic or rubber. It was appropriated as vermiculite of material such as "ms, shovels, dust is light fire immediate immediate immediate immediate immediate immediate. It is not light for smoke with the maker is not light fire immediate immediate immediate immediate immediate immediate. It is not light fire immediate immediate immediate immediate immediate immediate immediate. It is not light fire immediate immediate immediate immediate immediate immediate immediate. It is not light fire immediate immediate immediate immediate immediate immediate immediate immediate. It is not light fire immediate im	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water ssure self-co pmposition pr NTAL R leak, indivice gloves, resp pe protective prosand to so speedy dry" ans) and pla ple materials hazard area appropriate G & STC when handlir intended, no ntentional res	As in lemand) er spray ying wath fire colorway. For the spray ying wath fire colorway. For the spray in the s	any fire, and full proceeding to cool five to cool five the cool five the cool five protection of the cool for the cool five protection of the cool five protection of the cool five product the cool five equipments and plastic cool five equipments and plastic cool five equipments and plastic cool five equipments and protection of the cool five the coo	re-exposinto sto lution from the store of th	gear. Keed surface rage contains entering the full bunks to protections. RES In the full bunks to protection may be and protection and prot	ep contai es and t ainers be ig sewers ker gear ct against wear ap be require ective eye container erial using ner within n spill. S of area. tory prote	iners coo to protec ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwir Stop spi ection as Handle a	e Personal de la condition de	f large spon-combual. Do no materials er. away from ease if it cons warra	bills. ustik ot u (e.g) m s can ant.
1	Spills:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broop Large Spills or release, done with m Do not eat, container(s), contact is pool use and sto	as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind for any spill or plastic or rubber: Wear appropriate that we are upwind fire in mediate in media	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water sure self-co pmposition pr NTAL R leak, indivice gloves, respe p protective for sand to so speedy dry" ans) and pla ple materials hazard area appropriate proper G & STO when handling intended, no intentional res well-ventilat	As in lemand) er spray ying wath fire colorway. For the spray ying wath fire colorway. For the spray is a spray in the spr	any fire, and full proceeding to cool five to cool five the cool five the cool five the cool for the cool five the cool for the cool fo	re-exposinto sto lution fro must us apparatus deficience. EASUF spill clean and apparatus and place and place and place and including properties of the pro	gear. Keed surface rage contains entering the full bunks to protections. RES The must represent the full stop must and protection and prote	ep contai es and t ainers be ag sewers ker gear ct against wear ap be require container erial using ner within n spill. S of area. tory prote	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwir Stop spi ection as Handle a . Use ch	e Personal p	f large spon-combul. Do no materials er. away from ease if it coms warra	bills. ustible tot u telline t
1	Spills: Work & Hygiene Practices:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release. done with m 7 Do not eat, container(s). contact is por sunlight. Av	as for surrounding as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind in a cool, dry, not light fire in a cool, dry, not light fire upwinding and such as upwinding in a cool, dry, not light fire upwinding in a cool, dry, not light fire upwinding apparatures a cool, dry, not light fire upwinding apparatus.	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water sure self-co pmposition pr NTAL R leak, indivice gloves, respective self-co present to self-co present	As in lemand) er spray ying wath fire colorway. Fintained the roducts a ELEA duals invitation, eyequipme back up the to soak up the to soak up the colorway of the protective DRAG addition sidues will ded location.	any fire, and full proceeding to cool five to cool five to cool five the cool five the cool for the cool five the cool for	re-exposinto sto lution from the store of th	gear. Keed surface rage contains entering the full bunks to protections. RES The mup must ron may be and protection and prot	ep contai es and t ainers be ag sewers ker gear ct against wear ap be require container erial using ner within n spill. S of area. tory prote	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwir Stop spi ection as Handle a . Use ch	e Personal p	f large spon-combul. Do no materials er. away from ease if it coms warra	bills. ustible tot u telline t
1 2	Spills: Work & Hygiene Practices:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release, done with m 7 Do not eat, container(s), contact is pour such and sto sunlight. Av damage. To	as for surrounding as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind for a surrounding any spill or plastic or rubber. It wear appropriate the as vermiculite of material such as "ms, shovels, dustress is shovels, dustress is not light fire upwinding is not light fire upwinding is not light for smoke when used as assible. Wash unit or in a cool, dry, not demperatures a payoid unintention.	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water sure self-co pmposition pr NTAL R leak, indivice gloves, respective self-co present to self-co present	As in lemand) er spray ying wath fire colorway. Fintained the roducts a ELEA duals invitation, eyequipme back up the to soak up the to soak up the colorway of the protective DRAG addition sidues will ded location.	any fire, and full proceeding to cool five to cool five to cool five the cool five the cool for the cool five the cool for	re-exposinto sto lution from the store of th	gear. Keed surface rage contains entering the full bunks to protections. RES The mup must ron may be and protection and prot	ep contai es and t ainers be ag sewers ker gear ct against wear ap be require container erial using ner within n spill. S of area. tory prote	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwir Stop spi ection as Handle a . Use ch	e Personal p	f large spon-combul. Do no materials er. away from ease if it coms warra	bills. ustible tot u telline t
11	Spills: Work & Hygiene Practices: Storage & Handling:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release. done with m 7 Do not eat, container(s). contact is por sunlight. Av	as for surrounding as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind for a surrounding any spill or plastic or rubber. It wear appropriate the as vermiculite of material such as "ms, shovels, dustress is shovels, dustress is not light fire upwinding is not light fire upwinding is not light for smoke when used as assible. Wash unit or in a cool, dry, not demperatures a payoid unintention.	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water sure self-co pmposition pr NTAL R leak, indivice gloves, respective self-co present to self-co present	As in lemand) er spray ying wath fire colorway. Fintained the roducts a ELEA duals invitation, eyequipme back up the to soak up the colorway. Find the soak up the colorway of the protective DRAG addition sidues will ded location.	any fire, and full proceeding to cool five to cool five to cool five the cool five the cool for the cool five the cool for	re-exposinto sto lution from the store of th	gear. Keed surface rage contains entering the full bunks to protections. RES The mup must ron may be and protection and prot	ep contai es and t ainers be ag sewers ker gear ct against wear ap be require container erial using ner within n spill. S of area. tory prote	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwir Stop spi ection as Handle a . Use ch	e Personal p	f large spon-combul. Do no materials er. away from ease if it coms warra	bills. ustible tot u telline t
1	Spills: Work & Hygiene Practices: Storage & Handling:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release, done with m 7 Do not eat, container(s), contact is pour such and sto sunlight. Av damage. To Clean all spills or release.	as for surrounding as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind for a surrounding any spill or plastic or rubber. It wear appropriate the as vermiculite of material such as "ms, shovels, dustress is shovels, dustress is not light fire upwinding is not light fire upwinding is not light for smoke when used as assible. Wash unit or in a cool, dry, not demperatures a payoid unintention.	g materials. c (pressure-d t. Use water Avoid spra t runoff from natural water sure self-co pmposition pr NTAL R leak, indivice gloves, respective expression and pla ple materials hazard area appropriate proper self-ventional reserved in the mandling intended, no intentional reserved in the mandle well-ventilate above 120 °F all spraying k	As in lemand) er spray ying wath fire colorway. Fintained the roducts a ELEA duals invitation, eye equipme equipme to soak up that to soak up the color of the protective DRAG and the protective beautiful to so the color of the protective beautiful to so the color of the color of the protective beautiful to so the color of the co	any fire, and full proceeding to cool five to cool five to cool five the cool five the cool for the cool five the cool for	re-exposinto sto into into into into into into into in	gear. Keed surface rage contains entering the full bunks to protections. RES The mup must ron may be and protection and protection in the full bunks from the full b	ep contai es and t ainers be ag sewers ker gear et against wear ap be require ective eye ective eye erial using her within n spill. S of area. tory prote	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U g non-sp another stay upwir Stop spi ection as Handle a . Use ch ns) away	e Personal p	f large spon-combul. Do no materials er. away from ease if it coms warra	bills. ustible tot u telline t
1 2	Spills: Work & Hygiene Practices: Storage & Handling: Special Precautions:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release, done with m 7 Do not eat, container(s), contact is pour such and sto sunlight. Av damage. To Clean all spills or release.	as for surrounding as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind for a provided as upwind for the surrounding any spill or plastic or rubber. It wear appropriate the as vermiculite of material such as upwind fire in a condition of the surrounding for surroundin	g materials. c (pressure-dit. Use water Avoid sprate runoff from natural water self-coomposition proposition propo	As in lemand) er spray ying wath fire colorway. Fintained the roducts a ELEA duals invitation, eye equipme equipme to soak up that to soak up the color of the protective DRAG and the protective beautiful to so the color of the protective beautiful to so the color of the color of the protective beautiful to so the color of the co	any fire, and full proceeding to cool five to cool five to cool five the cool five the cool for the cool five the cool for	re-exposinto sto lution from the store of th	gear. Keed surface rage contains entering enteri	ep contai es and t ainers be ag sewers ker gear et against wear ap be require ective eye ective eye erial using her within n spill. S of area. tory prote	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U g non-sp another stay upwir Stop spi ection as Handle a . Use ch ns) away	e Personal p	f large spon-combul. Do no materials er. away from ease if it coms warra	bills. ustible tot u telline t
1 2 3	Spills: Work & Hygiene Practices: Storage & Handling: Special Precautions:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broop Large Spills or release, done with m 7 Do not eat, container(s), contact is pour contact is pour summing. Clean all spills 8. EXPO	as for surrounding as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind in the fire upwind unintention in the fire upwind	g materials. c (pressure-d t. Use water Avoid sprater runoff from natural water somposition pr NTAL R leak, indivice gloves, respective somposition pr en protective somposition and place protective somposition pr C & STO when handlire intended, non tentional resemble well-ventilate above 120 °F all spraying k NTROLS	As in lemand) er spray ying wat in fire core reway. Fintained the roducts are	any fire, and full proceeding to cool five to cool five to cool five the cool five the cool for	re-exposinto sto into into into into into into into in	gear. Keed surface rage contains entering the full bunks to protection of the full bunks to protection of the full bunks to protection of the full bunks to protect of the full bunks to prote	wear apperent authors being sewers wear apperent against wear apperent authors being sewers wear apperent within a spill. Sof area. Authors protestal using because within a spill. Sof area. Authors protestal authors, fall ances. First protestal authors and the second protestal authors are also authors are also authors are also authors and authors are also authors are	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another ection as Handle a . Use ch ns) away Protect co	e Personant and and arking reconditions to average of the conditions of the containers of the containe	f large spon-combual. Do no materials er. away from ease if it coms warranged goggles meat and s from ph	bills. ustible tot u telline t
1 2 3	Spills: Work & Hygiene Practices: Storage & Handling: Special Precautions:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release, done with m 7 Do not eat, container(s), contact is pour such and sto sunlight. Av damage. To Clean all spills or release.	as for surrounding as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind in the fire upwind unintention in the fire upwind	g materials. g (pressure-d t. Use water Avoid spra t runoff from natural water sure self-co pmposition pr NTAL R leak, indivice gloves, respe per protective of speedy dry ans) and plater ble materials hazard area appropriate G & STO when handlir intended, no intentional res well-ventilat above 120 °F al spraying k NTROLS	As in lemand) er spray ying wat in fire cooperway. Fintained the roducts are t	any fire, and full proceeding for to cool five to cool five to cool five the first fighters of the first fighters of the first fighters of the protection of the product of	re-exposinto sto lution from the store of th	gear. Keed surface rage contains entering enteri	wear apperent and the same of	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another ection as Handle a . Use ch ns) away Protect co	e Personal p	f large spon-combual. Do no materials er. away from ease if it coms warranged goggles meat and s from ph	bills. ustible tot u telline t
1 2 3	Spills: Work & Hygiene Practices: Storage & Handling: Special Precautions:	contained bruntil well af personal. F danger of b drinking wat NIOSH-appr hazardous c Before clea Equipment. Small Spills material suc water or a r plastic broot Large Spills or release. done with m 7 Do not eat, container(s). contact is post contact is post sunlight. Av damage. To Clean all spi 8. EXPO	as for surrounding as for surrounding apparatus for the fire is our light fire upwind. It is not light fire upwind in the fire upwind unintention in the fire upwind	g materials. g (pressure-d t. Use water Avoid spra t runoff from natural water sure self-co per self-c	As in lemand) er spray ying wat in fire congress. Fire contential in the conducts and the conducts are conducted and the conducts are conducted and the conducts are conducts and the conducts and the conducts are conducts and th	any fire, and full proceeding for to cool five to cool five to cool five the fire fighters or cooling for the fire fighters of the fire protection of the product of the fire product of the fire product of the fire fighters of the fire fire fighters of the fire fire fire fire fire fire fire fir	re-exposinto sto lution from the sto lution from the sto lution from the store into sto lution from the store into store	gear. Keed surface rage contains entering the full bunds to protect the full bunds to protect the full bunds to protect the full bunds and protect the full bunds from may be and protect the pup matter plastic limit away from sonnel out the full bunder present the full b	wear apperent against or require container erial using ner within n spill. S of area. tory prote cecessary. lation, fall tances. F	iners coo to protect ecause o s, drains including t potentia popropriate ed for clea ewear. U for later g non-sp another stay upwin Stop spi ection as Handle a . Use ch ns) away Protect co	e Personan-up of disposarion and and and answer disposarion in condition.	f large spon-combul. Do no materials er. away from ease if it cons warranged from product and some product a	cturi if e



Page 3 of 6 SDS-E-GX5S

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 6.3 SDS Revision Date: 5/15/2020 8. EXPOSURE CONTROLS & PERSONAL PROTECTION - cont'd Respiratory Protection: 8.3 No special respiratory protection is required under typical circumstances of use or handling. necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 8.4 Eve Protection: Avoid eye contact. Protective eyewear recommended. Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling large quantities (of this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. 8.5 Hand Protection: None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 8.6 Body Protection: No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Appearance Light yellow aerosol spray/mist 92 Odor Ethereal / hydrocarbon odor 9.3 Odor Threshold: NA 9.4 NA Melting Point/Freezing Point: 9.5 NΑ Initial Boiling Point/Boiling 9.6 NA Flashpoint: 9.7 NA Upper/Lower Flammability 9.8 NA Limits: 99 Vapor Pressure: 50 +/-5 psig @ 20 °C 9.10 Vapor Density: NA 9 11 Relative Density: $0.852 \pm 0.012 (7.10 \pm 0.1 \text{ lb/gal})$ 9 12 Solubility Partial to complete 9.13 Partition Coefficient (log Pow): NA Autoignition Temperature 9.14 NA 9.15 **Decomposition Temperature:** NA 9.16 Viscosity NΑ 9.17 Other Information: 0% VOC 10. STABILITY & REACTIVITY 10.1 Stability This product is stable. 10.2 Hazardous Decomposition Oxides of carbon (CO, CO₂) and sulfur (SO₂). Products: 10.3 Hazardous Polymerization: Will not occur. 10.4 Conditions to Avoid Open flames, sparks and high heat 10.5 Incompatible Substances: None known. 11. TOXICOLOGICAL INFORMATION Routes of Entry: Inhalation: Absorption: YES YES YES 11.1 Inaestion: Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is 11.2 available for some of the components of the product. 11.3 Acute Toxicity: See section 4.4 11.4 Chronic Toxicity See section 4.5 Suspected Carcinogen: This product does not contain any chemicals known to the State of California to cause cancer or other reproductive harm. For more information go to www.P65Warnings 11.6 Reproductive Toxicity: This product is not reported to produce reproductive toxicity in humans. Mutagenicity This product is not reported to produce mutagenic effects in humans. Embryotoxicity This product is not reported to produce embryotoxic effects in humans. Teratogenicity This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans. 11.7 Irritancy of Product See Section 4.2 11.8 Biological Exposure Indices: ΝE Physician Recommendations: 11.9 Treat symptomatically.



Page 4 of 6 SDS-E-GX5S

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 6.3 SDS Revision Date: 5/15/2020

		12. ECOLOGICAL INFORMATION		
12.1	Environmental Stability:	There is no specific data available for this product.		
12.2	Effects on Plants & Animals:	There are no specific data available for this product.		
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or f to overexposed aquatic life.		
		13. DISPOSAL CONSIDERATIONS		
13.1	Waste Disposal:	Products covered by this MSDS, in their original form, when disposed as waste, are considered non hazardous w according to Federal RCRA regulations (40 CFR 261). Disposal should be in accordance with local, state and fed		
13.2	Special Considerations:	California Waste Code: 331		
		44 TRANSPORTATION INFORMATION		
		14. TRANSPORTATION INFORMATION		
		r, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information. VICAO, IMDG and the CTDGR.		
14.1	49 CFR (GND):	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1000 mL) – until 12/31/2020 UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL)		
4.2	IATA (AIR):	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 500 mL) UN1950, AEROSOLS, NON-FLAMMABLE, 2.2 (LTD QTY, IP VOL ≤ 820 mL)		
4.3	IMDG (OCN):	UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL)		
4.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL) or MARK PACKAGE "LIMITED QUANTITY," "LTD QTY," or "QUANT LTÉE" or "QUANTITÉ LIMITÉE"		
4.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL)		
4.6	SCT (MEXICO):	UN1950, AEROSOLS, 2.2 (CANTIDAD LIMITADA, IP VOL ≤ 1000 mL)		
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.2 (LTD QTY, IP VOL ≤ 1000 mL)		
		15. REGULATORY INFORMATION		
15.1	SARA Reporting	This product does not contain any substances subject to SARA Title III, section 313 reporting requirements.		
15.2	Requirements: SARA TPQ:	There are no specific Threshold Planning Quantities for the components of this product.		
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.		
5.4	CERCLA Reportable Quantity:	NA		
15.5	Other Federal Requirements:	This material does not contain any hazardous air pollutants. This material does not contain any material listed as a Hazardous Substance under the CWA. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA.		
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List.		
15.7	State Regulatory Information: No ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substance List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesot Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY) Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substance List (WI).			
15.8	Other Requirements:	This product <u>does not</u> contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. For more information go to www.P65Warnings.ca.gov.		



Page 5 of 6

SDS Revision Date: 5/15/2020

SDS-E-GX5S

16. OTHER INFORMATION WARNING! PRESSURIZED CONATINER; MAY BURST IF HEATED. CAUSES EYE IRRITATION. Use only as 16.1 Other Information: directed. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Wash thoroughly after handling. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persist: Get medical advice/attention. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F. KEEP OUT OF REACH OF CHILDREN. 16.2 Terms & Definitions: See last page of this Safety Data Sheet. Disclaimer: 16.3 This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & CAIG Laboratories, Inc.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.



Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards



SDS Revision: 6.3





Page 6 of 6

SDS-E-GX5S

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 6.3

SDS Revision Date: 5/15/2020

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
IDLH	Immediately Dangerous to Life and Health
NOHSC	National Occupational Health and Safety Commission (Australia)
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	0 Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	



PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE STATE OF THE S	
D		H.	
Е			
F		H.	





OTHER STANDARD ABBREVIATIONS:

Carc	Carcinogenic		
Irrit	Irritant		
NA	Not Available		
NR	No Results		
ND	Not Determined		
NE	Not Established		
NF	Not Found		
SCBA	Self-Contained Breathing Apparatus		
Sens	Sens Sensitization		
STOT RE	STOT RE Specific Target Organ Toxicity – Repeat Exposure		
STOT SE	STOT SE Specific Target Organ Toxicity – Single Exposure		

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	AMMABILITY LIMITS IN AIR:		
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition		
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source		
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source		

HAZARD RATINGS:

	Minimal Hannel	
0	Minimal Hazard	FLAMMABILITY
1	Slight Hazard	\ \
2	Moderate Hazard	REACTIVITY
3	Severe Hazard	
4	Extreme Hazard	
ACD	Acidic	
ALK	Alkaline	
COR	Corrosive	/ ~~~~ ~~ ~
W	Use No Water	HEALTH 🔪
OX	Oxidizer	SPECIAL
TREFOIL	Radioactive	PRECAUTIONS

TOXICOLOGICAL INFORMATION:

	Lathal Dana (adida 0 limida) otiah bila 500/ afaha amada darimala
LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TCo, LCio, & LCo	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TLm	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System	
DOT	OT U.S. Department of Transportation	
TC	Transport Canada	
EPA	U.S. Environmental Protection Agency	
DSL	Canadian Domestic Substance List	
NDSL	Canadian Non-Domestic Substance List	
PSL	Canadian Priority Substances List	
TSCA	U.S. Toxic Substance Control Act	
EU European Union (European Union Directive 67/548/EEC)		
WGK	Wassergefährdungsklassen (German Water Hazard Class)	

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(A)	(2)		\odot	(49)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\limits		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment