

## **SBC6-103-161** Aliases (UPIN6103161000) KEMET, SBC6, Power, 10000 uH, 10%, 7.5mm

L + LL + Inductance

**General Information** Series SBC6 Style Through-Hole Description Radial Leaded, Ferrite Power Inductors DC-DC Converters, Nickel-Zinc (NiZn) Ferrite Core Features RoHS Yes Wire Leads Lead Core Ferrite Miscellaneous **Pin Lead Terminal** 

Specifications	
Inductance	10000 uH
Inductance Tolerance	10%
Temperature Range	-20/+105°C
Shielded	No
Current	0.16 Amps
DC Resistance	13.6 Ohms

Click here for the 3D model.

Dimensions	/
D	12mm MAX
L	18.5mm MAX
S	7.5mm +/-0.5mm
LL	6.5mm +/-1mm
F	0.8mm NOM

Packaging Specifications	1
Component Weight	5.875 g
Packaging	Bulk
Packaging Quantity	2000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.