	л Б л	m	D	0	ω	A		
CHARACTERSTICE Standard: Based on ML-DTL-38999 Series III. Shell Material :: Aluminiating Shell Material :: Based on ML-DTL-38999 Series III. Data :: Based on ML-DTL-38999 Series III. Based :: Based on ML-DTL-38999 Series III. Shell Material :: Based on ML-DTL-38999 Series III. Based :: Based on ML-DTL-38999 Series III. Based :: B	A 22.6 Max W presult presu				AS EXAMPLE			4
- Shell Material : Aluminum - Shell Material : Contact is : Contact is : Copper Alley - Contact Plating : Sold over copper Alley 0.8µm minimum - Oursbillty : Sold Astronger All	CHARACTERISTICS	Connector dimension Dim Nominal						
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 27.92 g ± 10% BASIC SERIES: 8D 7 - 13 W 04 S N CONTACT TYPE : Standard Crimp Contact SHELL TYPE : Standard Crimp Contact SHELL TYPE : Standard Crimp Contact SHELL SIZE : 13 PLATING : W = Olive drab Cadmium (Contact LAYOUT : 13-04) CONTACT TYPE : SOCKET(S00 Matings) CONTACT LAYOUT : 13-04	-Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum	B 23.82+0.1/-0.15 R 32.5Max S 34.9±0.4 W 2.2+0.9/-0.1		due to a use of the Product the Specifications issued by eith (professional recomment Co	s which does not comply er of the Parties or by a tl ndation, technical notice. untry Jurisdiction FR Not	with hird party) • & Control List		2
BASIC SERIES: 8D 7 13 W 04 S N BASIC SERIES: 8D 7 13 W 04 S N CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SHELL SIZE : 13 W 04 S N SCONTACT TYPE : SockET(500 Matings) SOURIAU This document is the property of SOURIAU.COM SOURIAU SOURIAU This document is the property of SOURIAU permission SOURIAU SOURIAU This document is the property of SOURIAU permission SOURIAU SOURIAU This document is the property of SOURIAU SOURIAU SOURIAU SOURIAU This document is the property of SOURIAU SOURIAU SOURIAU SOURIAU This document is the property of SOURIAU SOURIAU SOURIAU SOURIAU This document is the property of SOURIAU SOURIAU This document is the property of SOURIAU SOURIAU SOURIAU SOURIAU This document is the property of SOURIAU DRG N° SOURIAU SOURIAU SOURIAU This document is the property of SOURIAU DRG N° SOURIAU SOURIAU SOURIAU This document is the property of SOURIAU DRG N° SOURIAU SOURIAU SOURIAU SOURIAU This document is the property of SOURIAU SOURIAU	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours			First Release	3W04SN		MOD N°	
BASIC SERIES. ab 7 - 15 W 04 5 N In the series of the property of sources: 1 <td></td> <td></td> <td>Designed By:</td> <td>Date:</td> <td></td> <td></td> <td></td> <td></td>			Designed By:	Date:				
SHELL SIZE : 13 CONTACT TYPE : SOCKET(500 Matings) communicated without permission PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 13-04 FORMAT SOURIAU DRG N° SHEET	SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact	ORIENTATION : N	NA -{	Tolerances		859 This document is the proper SOURIAU		1
H G F E D C B A	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 13-04	A3	8D713	AU DRG N° W04SN-C		nission SHEET	

Г	D I	т (П		B	
	Contact Layout		Panel cutout JAM NUT RECEPTACLE (TYPE 7)		
4	$-X \begin{pmatrix} D \\ \oplus \\ \oplus \\ C \\ \oplus \\ \oplus \\ H \end{pmatrix} + \begin{pmatrix} \oplus \\ \oplus \\ \oplus \\ H \end{pmatrix} + X$			Λ	4
	Contacts (Insert arrangement 13-4) Location Contact position ID Location Contact position ID Contacts Location A +.000 (0.00) +.150 (3.81) B +.146 (3.71) +.035 (0.89) C +.000 (0.00) 083 (2.11) D 146 (3.71) +.035 (0.89)				
	Shell sizeArrangement no.Number of contactsSize contactsService ratingContact locationSupersedes location13-4416IAllMS20051-4		< ØC >		
ω			Dim Nominal B 24.26+0/-0. ØC 25.65+0.25,	25	3
			due to a use of the Pro the Specifications issued by	ble for any non-conformity or damage oducts which does not comply with r either of the Parties or by a third party mmendation, technical notice.)	
2				CountryJurisdiction & Control ListFRNot Listed	2
			A 29-09-2016 First Release	713W04SN	
			ISS DATE Latest modification - by		DD N°
			Designed By: Date: TITLE Alun	customer drawing ninium Receptacle 8D series	
_				al linear NPRDS / PROJECT ances: 859	1
			SOURIAU WWW.SOUR	communicated without permission	
					1EET 2/2
L	H G	FE	D C	B A]