



Electrical test:
 1. 100% short, open, miswire test
 2. Conduct resistance: 2 Ohm(max)
 3. Insulation resistance: 5Mohm(min)
 4. dielectric test: DC 300V

PIN ASSIGNMENT		
P1		P2
1	_____	1
2	_____	2
3	_____	3
4	_____	4
5	_____	5
6	_____	6
7	_____	7
8	_____	8
9	_____	9
10	_____	10
11	_____	11
12	_____	12
13	_____	13
14	_____	14
15	_____	15
16	_____	16
17	_____	17
18	_____	18
19	_____	19
20	_____	20
21	_____	21
22	_____	22
23	_____	23
24	_____	24
25	_____	25
SHELL	_____	SHELL

8	TIE	WHITE L=120mm	1	PCS
7	PE BAG	CLEAR SIZE:250*280*0.05mm PRINT BLACK*MADE IN CHINA*+*1PC*	1	PCS
6	TUBE	HEAT SHRINK TUBE BLACK OD1.5*20MM	2	PCS
5	SCREW	#4-40UNC TYPE L=30mm,NICKEL PLATED,MOLD:BEIGE ABS	4	PCS
4	Inner mold	CLEAR LD-PE	NA	g
3	Over mold	BEIGE, 40P PVC	NA	g
2	CONN	DB 25P MALE SODER TYPE PIN G/F SHELL NI-PLATED INSULATOR COLOR:BLUE	2	PCS
1	CABLE	NOUL 28AWG(7/0.12)*25C+D+AL/MY OD7.5mm JACKET BEIGE L=3000±15MM	1	PCS
No.	NAME	DESCRIPTION	Q'TY	UNIT

RoHS compliant
Unit: mm

Scale	Free				Date	Name	Customer-No.
TOLERANCE				Drawn	13.04.2019	Xavier	
				Approved	13.04.2019	Winnie	ASSMANN WSW-No. AK162-3
DIM	TOL						Drawing-No. ASS 8517 CA rev00
		① Drawn	13.04.2019				Xavier
Angle	TOL	Id.	Modification	Date	Name		