


ESD-R-47-P

Aliases (UECESDR47P0000)

KEMET, ESD-R, EMI Cores, Noise Suppression



General Information

Series ESD-R

Style Round - Toroidal

Cable Type Round Cable

Description EMI Core Solid, For Round Cables, Toroidal Cores, Coated Type

RoHS Yes

Qualifications UL94 V-2

Case Color Green

| Specifications | |
|---------------------|-------------------------|
| Temperature Range | -25/+85°C |
| Effective Frequency | 300 MHz (FM Band Range) |

Click here for the 3D model.

| Dimensions | y and the second se |
|------------|--|
| D | 48.5mm MAX |
| D2 | 26mm MIN |
| Т | 16mm MAX |

| Packaging Specifications | , |
|--------------------------|-----------|
| Packaging | Tray, Box |
| Packaging Quantity | 100 |
| Component Weight | 84.8 g |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.