



PRODUCT SPECIFICATION

TITLE

SERIAL ATA POWER CONNECTOR / 1.27mm PITCH

1.0 SCOPE

This Product Specification covers the mechanical, electrical and environmental performances requirements and test methods for Serial-ATA connector series products.

2.0 APPLICABLE DOCUMENTS AND SPECIFICATIONS

The following documents form a part of this specification to the extent specified herewith. In the event of conflict between the requirements of the specification and the product drawing, the product drawing shall take precedence. In the event of conflict between the requirements of the specification and the referenced documents, this specification shall take precedence.

2.1 EIA 364 Test Methods for Electronic and Electrical Component Parts

2.2 Serial ATA / High Speed Serialized at Attachment Specification

3.0 MATERIAL SPECIFICATIONS

3.1 Design and Construction

Connector shall be of the design, construction and physical dimensions specified on the applicable sales drawing.

3.2 Materials

- a) Contacts: Refer to respective Molex sales & engineering drawings
- b) Housing: Refer to respective Molex sales & engineering drawings
- c) Plating: Refer to respective Molex sales & engineering drawings

4.0 PERFORMANCE AND TEST DESCRIPTION

4.1 Performance requirement:

Connector shall be designed to meet the electrical, mechanical and environmental performances requirements specified in 5.0

4.2 VOLTAGE:

15V DC

4.3 CURRENT:

1.5A DC @25°C

4.4 TEMPERATURE

Operating Temperature Range: -35°C to +85°C (Without loss function)

Storage Temperature Range: -35°C to +85°C (Without loss function)

REVISION: B	ECR/ECN INFORMATION: EC No: SH2005-0052 DATE: 2004/08/10	TITLE: SERIAL ATA POWER CONNECTOR 1.27mm PITCH	SHEET No. 1 of 5
DOCUMENT NUMBER: PS-67490-002	CREATED / REVISED BY: Grate Ma 2004/08/10	CHECKED BY: Grate Ma 2004/08/10	APPROVED BY: Vincent 2004/08/10



PRODUCT SPECIFICATION

5.0 Test Requirements and Procedures.

5.1 ELECTRICAL REQUIREMENTS

	DESCRIPTION	TEST CONDITION	REQUIREMENT
5.1.1	Insulation Resistance	EIA 364-21 After 500 VDC for 1 minute, measure the insulation resistance between the adjacent contacts of mated and unmated connector assemblies.	1000 Mega ohms MINIMUM
5.1.2	Dielectric Withstanding Voltage	EIA 364-20 Method B Test between adjacent contacts of mated and unmated connector assemblies.	The dielectric shall withstand 500 VAC for 1 minute sea level
5.1.3	Contact Resistance (LLCR)	EIA 364-23 Subject mated contacts assembled in housing to 20 mV maximum open circuit at 100 mA maximum.	1. Initially 30 milliohms Max. 2. Resistance increased 15 milliohms Max. after stress
5.1.4	Contact current rating	1. Mount the connector to a test PCB 2. Wire power pins P1, P2, P8 and P9 in parallel for power 3. Wire ground pins P4, P5, P6, P10 and P12 in parallel for return 4. Supply 6A total DC current to the power pins in parallel, returning from the parallel ground pins (P4, P5, P6, P10 and P12) 5. Record temperature rise when thermal equilibrium is reached	1.5A per pin MINIMUM. The temperature rise above ambient shall not exceed 30 °C at any point in the connector when contact positions are powered. The ambient condition is still air at 25 °C.

REVISION: B	ECR/ECN INFORMATION: EC No: SH2005-0052 DATE: 2004/08/10	TITLE: SERIAL ATA POWER CONNECTOR 1.27mm PITCH	SHEET No. 2 of 5
DOCUMENT NUMBER: PS-67490-002	CREATED / REVISED BY: Grate Ma 2004/08/10	CHECKED BY: Grate Ma 2004/08/10	APPROVED BY: Vincent 2004/08/10



PRODUCT SPECIFICATION

5.2 MECHANICAL REQUIREMENTS

	DESCRIPTION		TEST CONDITION	REQUIREMENT
5.2.1	Visual and dimensional inspections		EIA 364-18 Visual, dimensional and functional per applicable quality inspection plan.	Meet product drawing requirements.
5.2.2	Insertion force		EIA 364-13 Measure the force necessary to mate the connector assemblies at a max. rate of 12.5 mm(0.492") per minute.	45 N MAXIMUM
5.2.3	Removal force	NONE LATCH	EIA 364-13 Measure the force necessary to unmate the connector assemblies at maximum rate of 12.5 mm(0.492") per minute.	10 N MINIMUM through 50 cycles
		LATCH	EIA 364-13 Apply a static 25N unmating test load	No damage and no disconnect through 50 cycles
5.2.4	Durability		EIA 364-09 50 cycles for internal cabled application; Test done at a Maximum rate of 200 cycles per hour.	No physical damage. Meet requirements of additional tests as specified in the test sequence

REVISION: B	ECR/ECN INFORMATION: EC No: SH2005-0052 DATE: 2004/08/10	TITLE: SERIAL ATA POWER CONNECTOR 1.27mm PITCH	SHEET No. 3 of 5
DOCUMENT NUMBER: PS-67490-002	CREATED / REVISED BY: Grate Ma 2004/08/10	CHECKED BY: Grate Ma 2004/08/10	APPROVED BY: Vincent 2004/08/10



PRODUCT SPECIFICATION

5.3 ENVIRONMENTAL REQUIREMENTS

	DESCRIPTION	TEST CONDITION	REQUIREMENT
5.3.1	Physical shock	EIA 364-27 Condition H Subject mated connector to 30 g's half-sine shock pulses of 11 msec duration. Three shocks in each direction applied along three mutually perpendicular planes for a total 18 shocks. See NOTE 2.	No discontinuities of 1 ms or longer duration. No physical damage.
5.3.2	Random vibration	EIA 364-28 Condition V Test letter A Subject mated connectors to 5.35 g's RMS. 30 minutes in each of three mutually perpendicular planes. See Note 2.	No discontinuities of 1 μ s or longer duration.
5.3.3	Humidity	EIA 364-31 Method II Test Condition A. Subject mated connectors to 96 hours at 40 $^{\circ}$ C with 90% to 95% RH	See NOTE 1
5.3.4	Temperature life	EIA 364-17 Test Condition III Method A. Subject mated connectors to temperature life at +85 $^{\circ}$ C for 500 hours.	See NOTE 1
5.3.5	Thermal shock	EIA 364-32 Test Condition I. Subject mated connectors to 10 cycles between -55 $^{\circ}$ C and +85 $^{\circ}$ C.	See NOTE 1
5.3.6	Mixed Flowing Gas	EIA 364-65, Class 2A Half of the samples are exposed unmated for seven days, then mated for remaining seven days. Other half of the samples are mated during entire testing	See NOTE 1

NOTE-

1. Shall meet EIA 364-18 Visual Examination requirements, show no physical damage, and shall meet requirements of additional tests as specified in the test sequences table.
2. Shock and vibration test fixture is to be determined by each user with connector vendors.

REVISION: B	ECR/ECN INFORMATION: EC No: SH2005-0052 DATE: 2004/08/10	TITLE: SERIAL ATA POWER CONNECTOR 1.27mm PITCH	SHEET No. 4 of 5
DOCUMENT NUMBER: PS-67490-002	CREATED / REVISED BY: Grate Ma 2004/08/10	CHECKED BY: Grate Ma 2004/08/10	APPROVED BY: Vincent 2004/08/10



PRODUCT SPECIFICATION

5.4 Group Test Item (3 pieces per group)

Test Sequence Groups	A	B	C	D	E
Sample group sizes	12	12	12	12	12
Examination of connector(s)	1,5	1,9	1,8	1,8	1,7
Low-Level Contact Resistance (LLCR)	2,4	3,7	2,4,6		4,6
Insulation resistance				2,6	
Dielectric withstanding voltage				3,7	
Current rating			7		
Insertion force		2			
Removal force		8			
Durability	3	4(a)			2(a)
Physical shock		6			
Vibration		5			
Humidity				5	
Temperature life			3		
Reseating (manually unplug/plug three times)			5		5
Mixed Flowing Gas					3
Thermal shock				4	

NOTE -

(a) Preconditioning, 20 cycles for the 50-durability cycle requirement.

(b) The insertion and removal cycle is at the Maximum rate of 200 cycles per hour.

6.0 PACKAGING

Parts shall be packaged to protect against damage during handling, transit and storage.

7.0 OTHER INFORMATION

REVISION: B	ECR/ECN INFORMATION: EC No: SH2005-0052 DATE: 2004/08/10	TITLE: SERIAL ATA POWER CONNECTOR 1.27mm PITCH	SHEET No. 5 of 5
DOCUMENT NUMBER: PS-67490-002	CREATED / REVISED BY: Grate Ma 2004/08/10	CHECKED BY: Grate Ma 2004/08/10	APPROVED BY: Vincent 2004/08/10