

STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED

C  $\bigcirc$ 

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE:

5000MΩ min.

1000V AC rms

ÓÒ

| COMBINATION D-SUB  |  | SW REFERENCE NO.: 630 COMBO ASSEMBLY |                  |       |
|--|--|--------------------------------------|------------------|-------|
|  |  | DRAWN: C.B                           | DATE: JAN. 01/20 | 19    |
|  |  | CHECKED:                             | DATE:            |       |
| EDAC INC<br>TORONTO, ONTARIO<br>CANADA<br>YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND<br>SHALL NOT BE REPRODUCED,OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1)               | SHEET 1 OF       | 2     |
|  |  | DRAWING NUMBER: 630-36W4250-4T4      |                  | ISSUE |
|  |  | PART NUMBER: 630-36W                 | 4250-4T4         | 1     |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



**ISSUE NUMBER** ORIGINAL (1)

