

.X ±0.25 .XX ±0.13


.XXX ±0.05

Ν	0	ΓE	S:	

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ GOLD PLATED	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	30A (CURRENT)	
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.	
INSULATOR RESISTANCE:	5000MΩ min.	

DIELECTRIC	
WITHSTANDING VOLTAGE:	

COMBINATION D-SUB





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN: C.B DATE: JAN. 01/2019   CHECKED: DATE:   SCALE: (IN C.A.D. 1:1) SHEET 1 OF 2   DRAWING NUMBER: 630-3W3-640-3NA ISSUE
SCALE: (IN C.A.D. 1:1) SHEET 1 OF 2
DRAWING NUMBER: 630-3W3-640-3NA ISSUE
PART NUMBER: 630-3W3-640-3NA 1

