


Data sheet | Item number: 787-876

Lead-acid AGM battery module; 24 VDC input voltage; 7.5 A output current;
1.2 Ah capacity; with battery control

www.wago.com/787-876



Similar to picture



Item description

Features:

- Lead-acid, absorbed glass mat (AGM) battery module for uninterruptible power supply (UPS)
- Can be connected to both 787-870 UPS Charger and Controller and 787-1675 Power Supply with integrated UPS charger and controller
- Parallel operation provides higher buffer time
- Built-in temperature sensor
- DIN-35-rail mountable
- Battery control (from manufacturing no. 216570) detects both battery life and battery type

Subject to changes. Please also observe the further product documentation!

Data Notes

Note

For parallel connection, please switch battery capacity setting to "OFF" in the UPS charger and controller.

Technical data

Input

Nominal input voltage U_{inom}	DC 24 V
---	---------

Output

Nominal output voltage U_{onom}	DC 24 V
Nominal output current I_{onom}	7.5 A

Energy storage system

Battery capacity	1.2 Ah
Charging current	$\leq 0.3 \text{ A}$
End-of-charge voltage	DC 27 V (25 °C)

Circuit protection

Internal fuse	T 15 A
---------------	--------

Safety and protection

Protection class	III
Protection type	IP20; per EN 60529
Pollution degree	2
Series operation	No
MTBF	> 500,000 h (per IEC 61709)
Service life (typ.)	5 / 4 / 2 a (20 / 30 / 40 °C)

Connection data

Connection type 1	Input/Output/Battery control
Connection technology	

Subject to changes. Please also observe the further product documentation!

CAGE CLAMP®

WAGO connector	WAGO 231 Series
Solid conductor	0.08 ... 2.5 mm ² / 28 ... 12 AWG
Fine-stranded conductor	0.08 ... 2.5 mm ² / 28 ... 12 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches
Cable length (max.)	3 m (Input, Output, Battery Control)

Physical data

Width	55 mm / 2.165 inches
Height	153 mm / 6.024 inches
Depth from upper-edge of DIN-rail	126.6 mm / 4.984 inches
Note (dimensions)	Height with connector

Mechanical Data

Mounting type	DIN-35 rail
---------------	-------------

Material Data

Weight	1980 g
--------	--------

Environmental requirements

Ambient temperature (operation)	-10 ... +40 °C
Ambient temperature (storage)	-20 ... +40 °C
Relative humidity	5 ... 80 % (no condensation permissible)

Standards and specifications

Conformity marking	CE
Standards/specifications	VdS-tested battery UL 508

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
eCl@ss 10.0	27-05-04-03
eCl@ss 9.0	27-05-04-03
ETIM 8.0	EC000357
ETIM 7.0	EC000357
PU (SPU)	1 pcs

Subject to changes. Please also observe the further product documentation!

Packaging type	box
Country of origin	DE
GTIN	4050821298243
Customs tariff number	85072080900

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant, No Exemption
SCIP notification number (Austria)	35ab2e59-bacb-4392-9887-576ff84b6de5
SCIP notification number (Belgium)	e4c5e777-34dc-4ce1-8ff5-b0c8c6a29bca
SCIP notification number (Bulgaria)	e7bd2258-d862-47b1-b90f-94af976b385a
SCIP notification number (Czech Republic)	1cadbc50-db83-42ed-9bae-9caf51d73f8
SCIP notification number (Denmark)	f08b16c7-5e67-4830-bdc2-847555db677b
SCIP notification number (Finland)	4f9f0273-73f8-4987-9908-fab577177f3f
SCIP notification number (France)	120ad21d-5464-4f71-8b04-64430d335c9c
SCIP notification number (Germany)	72bdfcdf-039a-4903-a04f-647d7a66dbd3
SCIP notification number (Hungary)	3c7304ff-e68d-4940-a26c-031c28a3a9ba
SCIP notification number (Italy)	65f71f76-8ea5-46d5-9032-31844fa05d8f
SCIP notification number (Netherlands)	27b8a7a0-71f4-4953-a258-df1fb592c439
SCIP notification number (Poland)	a39e1dfa-494b-46e3-ab0c-a5f0e54f8fa2
SCIP notification number (Romania)	ebab566d-d028-4149-83d8-c24378ed2007
SCIP notification number (Sweden)	31dbd2a0-4e36-455c-98b1-4241963e568c

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	EAC Brjansker Zertifizierungsstelle	TP TC 020/2011	RU_C-DE. AM02.B. 00093-19
	UL Underwriters Laboratories Inc.	UL 508	E255817 UR

Declarations of conformity and manufacturer's declarations

Certificate

Subject to changes. Please also observe the further product documentation!

Logo	Approval	Additional Approval Text	name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Optional accessories

Power supplies

	Uninterruptible power supply	
	Item no.: 787-870 UPS charger and controller; 24 VDC input voltage; 24 VDC output voltage; 10 A output current; LineMonitor; communication capability; 2,50 mm ²	www.wago.com/787-870
	Item no.: 787-1675 Switched-mode power supply with integrated charger and controller; Classic; 1-phase; 24 VDC output voltage; 5 A output current; communication capability; 10,00 mm ²	www.wago.com/787-1675

Marking accessories

	Marking strip	
	Item no.: 210-831 Marking strips; on reel; 2.3 mm wide; plain; Self-adhesive; white	www.wago.com/210-831
	Item no.: 210-832 Marking strips; on reel; 3 mm wide; plain; Self-adhesive; white	www.wago.com/210-832

Tool

	Operating tool	
	Item no.: 210-720 Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured	www.wago.com/210-720

Downloads

Documentation

Bid Text

787-876 docx - Datei	2019 Jul 12	docx 21.4 kB	Download
787-876 X81 - Datei	2019 Jul 12	xml 5.7 kB	Download
ausschreiben.de 787-876		URL	Download

Subject to changes. Please also observe the further product documentation!

Instruction Leaflet

Bleigel-Akku-Modul DC 24 V, 1,2 Ah	2022 Mar 23	pdf 588.5 kB	Download
---------------------------------------	-------------	-----------------	--------------------------

Additional Information

Disposal and Recycling Electrical and electronic equipment, Batteries, Packaging	V 1.1.0 2022 Aug 18	pdf 2.2 MB	Download
---	------------------------	---------------	--------------------------

CAD/CAE-Data

CAD data

2D/3D Models 787-876	URL	Download
----------------------	---------------------	--------------------------

CAE data

EPLAN Data Portal 787-876	URL	Download
---------------------------	---------------------	--------------------------

WSCAD Universe 787-876	URL	Download
------------------------	---------------------	--------------------------

ZUKEN Portal 787-876	URL	Download
----------------------	---------------------	--------------------------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 787-876 Lead-acid AGM battery module; 24 VDC input voltage; 7.5 A output current; 1.2 Ah capacity; with battery control	URL	Download
---	---------------------	--------------------------

Installation Notes

Subject to changes. Please also observe the further product documentation!