ſ	T Q T M	D	0	₿ >	
4					
ω			LAYOUT SHOWN AS EXAM	PLE	(
	Keying Shown as example				
	CHARACTERISTICS Connector dimension				
	-Standard : Based on MIL-DTL-38999 Series III       Dim       Nominal         -Shell Material       : Aluminium       ØS       41.7 Max         -Shell Plating       : Olive drab Cadmium       Z       31 Max         -Insulator       : Thermoplastic       VV THREAD       M31x1-6g         -Contacts       : Copper Alloy       : Silicon Elastomer		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum		Country FR	Jurisdiction & Control List Not Listed	2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D521W7	2AE	
	-Temperature Range <sub>:</sub> -65°C to +175°C -Salt Spray : 500 hours	A 10-10-2010	6 First Release		
_		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
		n Plug 8D series			
_	BASIC SERIES:     8D     5     -     21     W     72     A     E       SHELL TYPE : Plug with RFI Shielding     -     -     -     -     -     -     -     -     -     -	SCALE	General linear Tolerances:	NPRDS / PROJECT <b>859</b>	
	CONTACT TYPE     : Standard Crimp Contact       SHELL SIZE : 21     CONTACT TYPE : PIN(500 Matin	SOURIAU		it must not be reproduced	or
1	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 21	—	SOURIAU DI	communicated without permi	SHEET
		1			

	т	۵	г	m		0
		Contact louget				
		Contact Layout <b>72</b>				
		12				
4						
		2#4 Power				
	[	6#16 21-72	1			
	Ctc	X Y	-			
	Α	0 6.19	]			
	В	8.5 4.3				
	С	6.25 0	-			
ယ	D	8.5 -4.3	-			
	E F	0 -6.19 -8.5 -4.3	-			
	G	-6.25 0	-			
	Н	-8.5 4.3	]			
	1					
						SOURIAU shall not be liable for an
						due to a use of the Products wh
						the Specifications issued by either of (professional recommendat
						Countr
N						FR
						PN: 8D521V
						116 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumin
					SCALE	General linear Tolerances:
<u> </u>					NA	
					SOURIA	U WWW.SOURIAU.C
					FORMAT	SOURIAU
					A3	8D521W
L	Н	G	F	E	D	C

				4	
				3	
any non-conformity or damage which does not comply with er of the Parties or by a third party adation, technical notice.)					
		CUSTOMER DRAWING	MOD N°		
ninium Plug 8D series					
	859				
COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
	DRG N° 2AE-C		SHEET 2/2		
vv /	B	Α	-1-	J	
	2	. N			

ω