



.XX ±0.13 .XXX ±0.05



| ISSUE NUMBER | |
|--------------|---|
| ORIGINAL | 1 |





NOTES:


MATERIAL: HOUSING: SHELL: CONTACT:

DIELECTRIC

OPERATING TEMPERATURE:

WITHSTANDING VOLTAGE:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED




| POWER/CO-AX CONTACT RATING: | 30A (CURRENT) |
|--------------------------------|----------------|
| (IF PRESENT) | |
| SIGNAL CONTACT CURRENT RATING: | 5A PER CONTACT |
| SIGNAL CONTACT RESISTANCE: | 10mΩ MAX. |
| | |
| INSULATOR RESISTANCE: | 5000MΩ min. |

| | | SW REFERENCE NO.: 629 COMBO ASSEMBLY | | |
|--|--|--------------------------------------|------------------|-------|
| COMBINATION | COMBINATION D-SUB | | DATE: JAN. 01/20 | 19 |
| | | CHECKED: | DATE: | |
| EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: (IN C.A.D. 1:1) | SHEET 1 OF | 2 |
| | | DRAWING NUMBER: 629-21W | 1240-3T2 | ISSUE |
| | | PART NUMBER: 629-21W | 1240-3T2 | 1 |

-55°C ~ 125°C

1000V AC rms





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



