	<u>п</u> (		0	₿ 2	
ØS-					
			LAYOUT SHOWN AS EXAM	MPLE	
	Keying Shown as example				
CHARACTERISTICS  -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal				
-Shell Material       : Aluminium         -Shell Plating       : Nickel         -Insulator       : Thermoplastic         -Contacts       : Copper Alloy	ØS35.7 MaxZ31 MaxVV THREADM25x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Seals & Grommet : Silicon Elastomer		L	Country	Jurisdiction & Control List	
<ul> <li>-Contact Plating : Gold over copper Alloy 0.8µm minimum</li> <li>-Durability : 500 Mating cycles</li> <li>-Delivered without Souriau contacts</li> </ul>			PN: 8D517F0	Not Listed	
-Temperature Range65°C to +200°C					
-Salt Spray : 48 hours		A 14-10-2016			
Mass : 31.38 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
		TITLE	TITLE Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 17 F	08 S C L	SCALE	General linear Tolerances:	NPRDS / PROJECT <b>859</b>	
SHELL TYPE : Plug with RFI Shielding         CONTACT TYPE : Standard Crimp Contact	Delivered W/O Con ORIENTATIO			This document is the pr	operty of
SHELL SIZE : 17	CONTACT TYPE : SOCKET(500 Ma		WWW.SOURIAU.CO	M it must not be reproduced without p	
			SOURIAU D		SHEET
PLATING : F = Nickel	CONTACT LAYOUT :	A3	JUUNIAU D	אי טאי	SHEET

_	т	۵	וד-	m		0	
		Contact Layout					
4	-x (	$ \begin{array}{c} & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & $					
_	Conta position A B C C D E F	Contacts           (Insert arrangement 17-8)           Location           X-axis         Y-axis           (mm)         (mm)           +.000 (0.00)         +.236 (5.99)           +.128 (3.25)         +.086 (2.18)           +.230 (5.84)        078 (1.96)           +.094 (2.39)        216 (5.49)					
ω	size no. cor						
						SOURIAU shall not be liable due to a use of the Produ the Specifications issued by eit (professional recomm	ucts w ither c
N						PN: 8D5	Count FR
					A 14-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:	
					TITLE	Alı	umir
					SCALE	General lin Toleranc ±	ces:
					SOURIA	U WWW.SOURIA	۱U.C
				_	FORMAT A3	SOUR 8D51	
	Н	G	F	E	D	C	

	ω		A		_	
					4	
					3	
	on conformit	. or domoo				
whicl r of tł	ion-conformit h does not co ne Parties or b n, technical no	mply with by a third pa				
ntry R	Jurisd	iction & Co Not Liste			2	
	8SCL					
		CUSTON		MOD N°		
customer drawing inium Plug 8D series						
r		NPRDS / PROJECT				
859						
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
	DRG N° SCL-C	<u> </u>		SHEET 2/2		
	B		A		L	