

www.tripplite.com



# VGA with Audio over Cat5/Cat6 Extender Kit, Wallplate Transmitter and Receiver with EDID, 1920x1440 at 60Hz, Up to 1000-ft.

MODEL NUMBER: B130-101A-WP-1







#### Description

Tripp Lite's B130-101A-WP-1 allows you to extend a 1920 x 1440 (60Hz) Video and Audio signal up to 500 ft., or a 1024 x 768 (60Hz) Video and Audio signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's N022-01K-GY (Cat5) and N222-01K-GY (Cat6). For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite P524-01K. A maximum resolution of 1920 x 1440 (60Hz) is supported. The remote (Receiver) unit features built-in Equalization and Gain controls to adjust the video image. Kit includes local (Transmitter) and remote (Receiver) RJ45 type wallplates, which allow you to use standard patch cable, eliminating the need for a 110 punchdown connection. A VGA + Audio "Y" cable is included for use with the local unit, allowing for the connection of a local monitor and speakers. Ideal for digital signage situations, such as retail, schools, churches, etc.

### **Features**

- Extends a 1920 x 1440 (60Hz) Video and Audio signal up to 500 ft., or a 1024 x 768 (60Hz) Video and Audio signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's N022-01K-GY (Cat5) and N222-01K-GY (Cat6)
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite P524-01K
- A VGA + Audio "Y" cable is included for use with the local unit, allowing for the connection of a local monitor and speakers
- RJ45 type wallplates allow you to use standard patch cable, eliminating the need for a 110 punchdown
  connection.
- The remote (Receiver) unit features built-in Equalization and Gain controls to adjust the video image
- Ideal for digital signage situations, such as retail, schools, churches, etc.

#### **Highlights**

- Extends a 1920 x 1440 (60Hz)
   Video and Audio signal up to
   500 ft., or a 1024 x 768 (60Hz)
   Video and Audio signal up to
   1,000 ft., when using 24Awg,
   Solid Wire Cat5e/6 cable, such as Tripp Lite's N022-01K-GY
   (Cat5) and N222-01K-GY (Cat6)
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite P524-01K
- RJ45 type wallplates allow you to use standard patch cable, eliminating the need for a 110 punchdown connection
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Package Includes

- Local (Transmitter) wallplate
- Remote (Receiver) wallplate
- VGA + Audio "Y" cable
- Mini-Screwdriver for EQ/Gain adjustment
- Wallplate Screws
- (x2) External Power Supply
   (Input: 100-240V, 50/60Hz, 0.5A
   Output: 5V, 2A)
- Owner's Manual



• Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## **Specifications**

OVERVIEW		
UPC Code	037332160188	
0.0000	60.002.100.100	
PHYSICAL		
Shipping Dimensions (hwd / cm)	16.00 x 5.72 x 25.65	
Shipping Dimensions (hwd / in.)	6.30 x 2.25 x 10.10	
Shipping Weight (kg)	0.45	
Shipping Weight (lbs.)	1.00	
COMMUNICATIONS		
Max 1024 x 768 Range (ft)	1000	
Max 480P Range (ft)	1000	
Max 1440 x 900 Range (ft)	500	
Max 1080i Range (ft)	500	
Max 1080P Range (ft)	500	
Max 1920 x 1440 Range (ft)	500	
Max 480i Range (ft)	1000	
Max 640 x 480 Range (ft)	1000	
Max 800 x 600 Range (ft)	1000	
Max 1600 x 1200 Range (ft)	500	
Max 1920 x 1200 Range (ft)	500	
Max 720P Range (ft)	500	
CONNECTIONS		
Ports	1	
Side A - Connector 1	HD15 (FEMALE)	
Side A - Connector 2	RJ45 (FEMALE)	
Side A - Connector 3	3.5MM (FEMALE)	
Side B - Connector 1	HD15 (FEMALE)	
Side B - Connector 2	3.5MM (FEMALE)	
Side B - Connector 3	RJ45 (FEMALE)	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

FEATURES & SPECIFICATIONS	
Technology	VGA/SVGA; Stereo Audio
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>