IPC ASSOCIATION CONNECTINE ELECTRONICS INDUSTRIE	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				nder both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				Form Type * Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					erials and N	ials and Mfg Information			
upplier Inforn	nation														
Company name*			Company unique ID			ι	Unique ID Authority					Response Date*			
nsemi											2023-0	2023-06-08			
Contact Name			Title - Contact			F	Phone - Contact*				Email	Email - Contact*			
Product-Env-Stewa	ards		Product Enviro Compliance			1	NA				Produ	Product-Env-Stewards@onsemi.com			
uthorized Represe	entative*		Title - Representative			F	Phone - Representative*				Email	Email - Representative*			
Product-Env-Stewa	ards	Product Enviro Compliance]	NA				Produ	Product-Env-Stewards@onsemi.com				
Requesto	Requester Item Number M		Mfr Item Number Mfr Item Name			Effect		Versi	on	Manufacturing Site		Weight*	UOM	Unit Type	
		LE25S16	225S161XATAG 16M bit serial flash m 120nm, WLCSP		h memory, Vcc	=1.8V,	2023-06-08			PHM		4.26	mg	Each	
Ianufacturing	Process Information	n													
Terminal Plating / Grid Array Material			Ferminal Base Alloy J-STD-020 MSL		Rating	Peak Process Body Temperature Max Time at Pea			k Temperature Number of Reflow Cycles						
SnAgCu			CU Alloy 1			260	C 30		seco	onds 3					
omments															
vel 1 - maximum t	ime at peak temperature	during sold	dering is 10-3	30 seconds											
or more informati	on regarding material co	mposition p	olease refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	3.64	mg	Supplier	Silicon (Si)	7440-21-3		3.64	mg
Electrode	0.11	mg	Supplier	Copper (Cu)	7440-50-8		0.11	mg
Protection coat	0.17	mg	Supplier	Epoxy resins	129915-35-1		0.17	mg
Solder Ball	0.34	mg	Supplier	Silver (Ag)	7440-22-4		0.0102	mg
			Supplier	Tin (Sn)	7440-31-5		0.3281	mg
			Supplier	Copper (Cu)	7440-50-8		0.0017	mg