


MR-2032 Aliases (UNFMR2032XXXXX)



Specifications Voltage AC 250 VAC 1500 VAC Withstanding Voltage 1 Min. Line to Voltage Ground Rated Current 3 A (AC/DC) Temperature -20/+60°C Range 300 MOhms MIN Insulation 500 VDC 1 Min. Line Resistance To Ground

30 K Self-Temperature Rise Max.

Click here for the 3D model.

Dimensions		
L	49mm NOM	
W	40mm NOM	
Н	27mm NOM	

Packaging Specifications			
Packaging	Tray, Box		
Packaging Quantity	100		
Component Weight	35 g		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

KEMET, MR, EMI/RFI Filters, Noise Suppression, 250 VAC, 3 A

MR

Plastic Box

Noise Filters

UL, CSA

Faston

With Exemptions

General Information

Series

Style

RoHS Qualifications

Description

Miscellaneous

Terminal Type