ш.			೧ (
Z					
			LAYOUT SHOWN AS EXAMPL	E	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension				
Standard : Based on MIL-DTL-38999 Series III	Dim Nominal				
-Shell Material : Aluminium	ØS 29.4 Max Z 31 Max		SOURIAU shall not be liable for any non-c		
-Shell Plating : Black Zinc Nickel	VV THREAD M18x1-6g	due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party			
-Insulator : Thermoplastic			(professional recommendation, tec		
-Contacts : Copper Alloy					
-Seals & Grommet : Silicon Elastomer			Country FR	Jurisdiction & Control List Not Listed	
-Contact Plating : Gold over copper Alloy 0.8µm minimum			FR	NOT LISTED]
-Durability : 500 Mating cycles		PN: 8D513Z98SAL			
-Delivered without Souriau contacts					
-Temperature Range : -65°C to +175°C		A 19-10-2016 First	Release		
-Salt Spray : 500 hours -Mass : 21.7 g ± 10%		ISS DATE Lat	test modification - by		MOD N°
Mass : 21.7 g ± 10%		Designed By:	Date:	CUSTOMER DRAWING	mobili
		TITLE	Aluminium	Plug 8D series	
	1 1 1	SCALE	1 General linear		
	98 S A L		Tolerances:	NPRDS / PROJECT 859	
SHELL TYPE : Plug with RFI Shielding	Delivered W/O Contac	ts NA		This document is the pro	perty of
CONTACT TYPE : Standard Crimp Contact	ORIENTATION :	A SOURIAU	WWW.SOURIAU.COM	SOURIAU	
	CONTACT TYPE : SOCKET(500 Mating			it must not be reproduc communicated without pe	
SHELL SIZE : 13		—			
	CONTACT Ι ΔΥΟΙ ΙΤ· 13-0	98 FORMAT	SULIBIALLING		SHEET
SHELL SIZE : 13 PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 13-9	A3	SOURIAU DRO 8D513Z98SA		1/2

_	т	۵	н г	m		0
		Contact Layout				
4		$x_{1}^{(a)} \bigoplus_{F}^{A} \bigoplus_{B}^{(a)} \bigoplus_{B}^{(a)} \bigoplus_{F}^{(a)} \bigoplus_{F}^{(a)} \bigoplus_{D}^{(a)} \bigoplus_{D}^{(a)} \bigoplus_{F}^{(a)} \bigoplus_{D}^{(a)} \bigoplus_{D}^{(a)} \bigoplus_{F}^{(a)} \bigoplus_{D}^{(a)} \bigoplus_{D}^$				
	Conti positi A B C C C C C C C C C C C C C C C C C C	In ID (mm) (mm) +.000 (0.00) +.195 (4.95) +.125 (3.18) +.150 (3.81) +.133 (490) +.030 (0.76) +.164 (4.17) 105 (2.67) +.000 (0.00) 135 (3.43) 164 (4.17) 105 (2.67) 193 (490) +.030 (0.76) 125 (3.18) +.150 (3.81) +.026 (1.65) 015 (0.38)				
ယ	Shell Arrangement No. c 13 -98	lumber of contacts contacts rating location Supersedes 10 20 I All MS20051-98				
						SOURIAU shall not be liable for an due to a use of the Products wi the Specifications issued by either o (professional recommenda
N						Counti FR
						PN: 8D5132
					A 19-10-20	16 First Release
_					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
<u> </u>					SCALE NA	General linear Tolerances:
					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU
L	Н	G	F	E		8D513Z9
					V	

Φ			A			
						4
						3
any non-confo which does no r of the Parties dation, technic	ot compl s or by a cal notic	ly with third part e.)				
R B BZ98SAL	N	on & Cont lot Listed				2
				 	OD N°	
CUSTOMER DRAWING						
iinium Plug 8D series						
r	NPRDS / PROJECT					
859 This document is the property of						1
.COM	COUDIAL					
U DRG N	۱°			5	HEET	
Z98SAL-	С				2/2	
В			А			