

CATTEN-01R5  
1.5dB Attenuator  
SMA 50 Ohm  
DC to 3 GHz



Temperature Range: -40°C to +85°C  
 Rated Power: 1 Watt Max  
 Frequency Range: DC to 3 GHz  
 VSWR: 1:1.3 Max  
 Impedance: 50 Ohms  
 Attenuation Tolerance: ±0.3 dB Typical

The Attenuator offers end users a rugged SMA attenuator housing for easy connection. The CATTEN-01R5 provides 1 Watt of power dissipation. Tolerance matching is used to provide superior temperature tracking to individual components. Attenuator frequency range is from DC to 3 GHz.

Test	Condition of Test	Test Results	
		0.5dB to 5dB	6dB to 20dB
Endurance Test per EIA 575-3.14	1000 hrs at 70°C, 1.5 hrs "ON", 0.5 hrs "OFF"	± 0.2 dB	± 0.3 dB
Overload	Per EIA 575-3.6 Short time overload	± 0.2 dB	± 0.3 dB
Thermal Shock	Per EIA 575-3.5	± 0.2 dB	± 0.3 dB
Moisture Resistance	Per EIA 575-3.10	± 0.2 dB	± 0.3 dB
High Temperature Exposure	Per EIA 575-3.7	± 0.2 dB	± 0.3 dB
Low Temperature Exposure	Per EIA 575-3.12	± 0.2 dB	± 0.3 dB

**Product Control:**

Crystek Part Number:	CATTEN-01R5	Release Date:	24-Jan-2022
Revision Level:	D	Responsible:	K. Piotrowicz

# CATTEN-01R5

## 1.5dB Attenuator


### SMA 50 Ohm

### DC to 3 GHz



Part Number	Attenuation (dB)	Max Power (Watts)
CATTEN-01R0	1.0	1
<b>CATTEN-01R5</b>	<b>1.5</b>	<b>1</b>
CATTEN-02R0	2.0	1
CATTEN-03R0	3.0	1
CATTEN-04R0	4.0	1
CATTEN-05R0	5.0	1
CATTEN-06R0	6.0	1
CATTEN-07R0	7.0	1
CATTEN-08R0	8.0	1
CATTEN-09R0	9.0	1
CATTEN-0100	10.0	1
CATTEN-0150	15.0	0.5
CATTEN-0180	18.0	0.5
CATTEN-0200	20.0	0.5

1.5 dB Data		Return Loss	
Freq. (MHz)	Atten (dB)	Male (dB)	Female (dB)
0.3	1.45	74	66
0.5	1.45	74	66
0.8	1.45	74	66
1.0	1.44	74	66
5.0	1.44	70	66
10.0	1.44	69	65
20.0	1.43	63	63
50.0	1.45	57	56
100.0	1.45	51	50
200.0	1.45	46	44
300.0	1.48	43	42
400.0	1.49	41	40
500.0	1.48	39	39
600.0	1.49	38	37
700.0	1.50	36	36
800.0	1.49	35	35
900.0	1.51	34	34
1000.0	1.49	33	33
1500.0	1.54	28	29
2000.0	1.62	23	24
2500.0	1.56	20	20
3000.0	1.78	18	17


**Product Control:**

Crystek Part Number:	CATTEN-01R5	Release Date:	24-Jan-2022
Revision Level:	D	Responsible:	K. Piotrowicz