

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

8-Outlet Vertical Power Strip, 120V, 15A, 10-ft. Cord, 5-15P, 24 in.

MODEL NUMBER: PS240810









• The PS240810 power strip provides horizontal or vertical power distribution for rackmount, raceway and workbench applications in a convenient 24-inch mountable housing.

Description

The PS240810 provides a 15-amp, 120v power strip with 8 standard NEMA 5-15 outlets in a rugged, all-metal, mountable housing. It allows for both vertical and horizontal mounting, making it ideal for a variety of uses including office, rackmount, workbench, industrial and telecom applications. With a NEMA 5-15P, 10-ft. power cord, you don't have to install the PS240810 next to outlets you already have; it can be mounted across the room and deliver reliable service where you need it most. A lighted and covered On/Off switch helps prevent accidental shut-offs, while a 15-amp circuit breaker guards against dangerous circuit overloads. Its sturdy all-metal extruded aluminum housing stands up to demanding network, laboratory or factory environments.

Features

Multi-Outlet Power Distribution:

Vertical or Horizontal Mounting:

Extra Long Power Cord:

Premium Safety Features:

Heavy-Duty Housing:

Highlights

- Ideal for applications needing multiple convenience outlets for powering a variety of electronic equipment24-in mountable housing with 8 standard NEMA 5-15R outlets and a 10 ft. power cord
- Lighted, covered On/Off switch and 15-amp circuit breaker
- Sturdy construction and heavyduty, all-metal housing

Package Includes

- PS240810
- Mounting hardware
- · Instruction manual



Specifications

OverVIEW OUTPUT Frequency Compatibility 60 H2 Output (Watts) 1800 Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Outlet Spacing 24 8 in. INPUT New Journal Input Voltage(s) Supported 120V AC Recommended Electrical Service 15A 120V Input Card Gauge Type 14gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Card Length (ft) 10 Input Cord Length (m) 3.05 Inguit Cord Length (m) 3.05	-		
Output Watts) 60 Hz Output (Watts) 1800 Output (Watts) 1800 Output Recaptacles (8) 6-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Outlet Spacing 2.48 in. Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 120 V C Recommended Electrical Service 15A 120V Input Cord Gauge Type 14 gauge, SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTES Switches Lighted 2 position switch controls power to all outlets Looking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Weight (bs.) 2.90 Shipping Weight (kg) 1.32	OVERVIEW		
Frequency Compatibility 60 Hz Output (Wats) 1800 Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Outlet Spacing 2.48 in. Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 15A 120V Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTUS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / cm.) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	UPC Code	037332187512	
Output (Watts) 1800 Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Outlet Spacing 2.48 in. Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 15A 120V Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & COVELS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	OUTPUT		
Output Receptacles (8) 5-15R Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Outlet Spacing 2.48 in. Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 15A 120V Input Cord Gauge Type 15A 120V Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / in.) 6.35 x 11.68 x 71.63 Shipping Weight (fts.) 2.90 Shipping Weight (kg) 1.32	Frequency Compatibility	60 Hz	
Circuit Breaker (amps) 15 Transformer Accommodation (4) Yes Outlet Spacing 2.48 in. Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 15A 120V Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTES Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Weight (fts.) 2.90 Shipping Weight (kg) 1.32	Output (Watts)	1800	
Transformer Accommodation (4) Yes Outlet Spacing 2.48 in. Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 15A 120V Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTELS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Output Receptacles	(8) 5-15R	
Outlet Spacing 2.48 in. Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 15A 120V Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTOLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental tum-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Circuit Breaker (amps)	15	
Right-Angle Outlets No INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 15A 120V Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTOLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Transformer Accommodation	(4) Yes	
INPUT Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 15A 120V Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTOLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Outlet Spacing	2.48 in.	
Nominal Input Voltage(s) Supported 120V AC Recommended Electrical Service 15A 120V Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTOLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Right-Angle Outlets	No	
Recommended Electrical Service 15A 120V Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	INPUT		
Input Cord Gauge Type 14 gauge; SJT Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No VSER INTERFACE, ALERTS & CONTOLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (kg) 1.32	Nominal Input Voltage(s) Supported	120V AC	
Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Recommended Electrical Service	15A 120V	
Input Plug Type NEMA 5-15P Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Input Cord Gauge Type	14 gauge; SJT	
Input Cord Length (ft.) 10 Input Cord Length (m) 3.05 Integrated Cord Clip No USER INTERFACE, ALERTS & CONTOLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Voltage Compatibility (VAC)	120	
Input Cord Length (m) Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Input Plug Type	NEMA 5-15P	
Integrated Cord Clip No USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Input Cord Length (ft.)	10	
USER INTERFACE, ALERTS & CONTROLS Switches Lighted 2 position switch controls power to all outlets Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Input Cord Length (m)	3.05	
Switches Lighted 2 position switch controls power to all outlets Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Integrated Cord Clip	No	
Locking Switch Cover Transparent on/off switch cover prevents accidental turn-off PHYSICAL Shipping Dimensions (hwd / in.) 2.50 x 4.60 x 28.20 Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	USER INTERFACE, ALERTS & CONTROLS		
PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Switches	Lighted 2 position switch controls power to all outlets	
Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off	
Shipping Dimensions (hwd / cm) 6.35 x 11.68 x 71.63 Shipping Weight (lbs.) 2.90 Shipping Weight (kg) 1.32	PHYSICAL		
Shipping Weight (lbs.) Shipping Weight (kg) 1.32	Shipping Dimensions (hwd / in.)	2.50 x 4.60 x 28.20	
Shipping Weight (kg) 1.32	Shipping Dimensions (hwd / cm)	6.35 x 11.68 x 71.63	
· · · · · · · · · · · · · · · · · · ·	Shipping Weight (lbs.)	2.90	
Unit Dimensions (hwd / in.) 24.20 x 1.25 x 1.5	Shipping Weight (kg)	1.32	
	Unit Dimensions (hwd / in.)	24.20 x 1.25 x 1.5	
Unit Dimensions (hwd / cm) 61.97 x 3.18 x 3.8	Unit Dimensions (hwd / cm)	61.97 x 3.18 x 3.8	





Unit Weight (lbs.)	2.16
Unit Weight (kg)	0.98
Material of Construction	Aluminum
Included Mounting Accessories	Includes mounting clips
Integrated Keyhole Mounting Slots	No
Receptacle Color	Black
Color (AC Line Cord)	Black
Color	Silver
Form Factors Supported	Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications
Outlets Measurement (Center to Center)	63mm
Anti-Microbial Protected	No
CERTIFICATIONS	
UL1363 (Power Tap)	UL1363
Canada	cUL
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies