

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMB	ER
ORIGINAL	

(1)





6.10 田 + 11.00

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

(IF PRESENT)

OPERATING TEMPERATURE:

.X ±0.25 .XX ±0.13 .XXX ±0.05

50Ω (IMPEDANCE) POWER/CO-AX CONTACT RATING:

-55°C ~ 125°C

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:


STEEL, NICKEL PLATED

THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, GOLD FLASH PLATED

5000MΩ min.

1000V AC rms



		SW REFERENCE NO.: 629 COMBO ASSEMBLY			
COMBINATION	COMBINATION D-SUB		DATE: JAN. 01/20	19	
			DATE:		
EDAC INC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
		DRAWING NUMBER: 629-3W3-	-240-5N5	ISSUE	
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 629-3W3-	-240-5N5	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

