


KHA102KP43CHAAA

Obsolete

KHA, Ceramic, 1000 pF, 10%, 2000 VDC, X7R, Lead Spacing = 5mm



Dimensions		
D	10.5mm MAX	
Т	4.5mm MAX	
S	5mm NOM	
LL	25mm +/-1mm	
F	0.6mm +/-0.1mm	

Packaging Specifications		
Packaging	Bulk, Bag	

General Information			
Series	KHA		
Style	Radial Disc		
RoHS	Yes		
Termination	Tin		
Failure Rate	N/A		
AEC-Q200	No		
Miscellaneous	Climate Category: 55/125/21.		

Specifications	
Capacitance	1000 pF
Capacitance Tolerance	10%
Voltage DC	2000 VDC
Dielectric Withstanding Voltage	4000 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	X7R
Dissipation Factor	2.5%
Insulation Resistance	10 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.