



Data

Connection data

Solid conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Fine-stranded conductor	0.08 ... 2.5 mm ² / 28 ... 14 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 inches

Physical data

Width	12 mm / 0.472 inches
Depth	74.3 mm / 2.925 inches

Mechanical Data

Pluggable connector	Pluggable
---------------------	-----------

Material Data

Color	yellow
Fire load	0.204 MJ
Weight	11.2 g

Environmental requirements

Ambient temperature (operation)	0 ... +55 °C
---------------------------------	--------------

Subject to changes. Please also observe the further product documentation!



Ambient temperature (storage)	-25 ... +85 °C
Protection type	IP20

Commercial data

Product Group	15 (I/O System)
eCl@ss 10.0	27-24-26-92
eCl@ss 9.0	27-24-26-92
ETIM 8.0	EC002584
ETIM 7.0	EC002584
PU (SPU)	25 pcs
Packaging type	box
Country of origin	CN
GTIN	4045454372064
Customs tariff number	85366990990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Documentation

Manual

System Manual WAGO I/O System 750/753 Decentralized Automation Technology	V 3.3.0 2023 May 4	pdf 8.8 MB	Download
--	-----------------------	---------------	----------

Bid Text

753-120 X81 - Datei	2019 Feb 19	xml 3.1 kB	Download
753-120 docx - Datei	2019 Jan 9	docx 13.8 kB	Download

CAD/CAE-Data

CAE data

WSCAD Universe 753-120	URL	Download
------------------------	-----	----------

EPLAN Data Portal 753-120

Subject to changes. Please also observe the further product documentation!



[URL](#)

[Download](#)

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 753-120

[URL](#)

[Download](#)

Plug; Safety

Installation Notes

Product family

WAGO I/O System 750/753

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.