



## PL518 Series 5mm LED Snap-in Holder

### Features

- \*Snap-in Design Requires no Hardware
- \*Mounting Hole 6.35 mm (0.25")
- \*Housing Material Black Nylon UL94V-2
- \*1 Yellow LED with Color Diffused Lens used
- \*26AWG 6" (+) Red and (-) Black Wire Leads
- \*RoHS Compliant

### Absolute Maximum Ratings at T<sub>A</sub> = 25°C

Reverse Voltage (<100μA).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to +85°C
Storage Temperature Range.....	-25°C to +100°C
Soldering Temperature (1.6 mm below body).....	260°C for 5 seconds

### Electrical & Optical Characteristics at T<sub>A</sub> = 25°C

Part Number	Emitting Color	Chip Material	Peak Wave Length	View Angle 2θ ½	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
					Typ	Max	Min	Typ
Color Diffused Lens			nm	Deg	Typ	Max	Min	Typ
PL518-1Y01-2	Yellow	GaAsP	585	50°	2.1	3.0	10.0	17.0

All dimensions are in **Millimeters**. Tolerance is ± 0.25mm unless otherwise specified.

