

FFA.00.250.CTAK42

SUMMARY

Wires

Coax	1
Series	00
Termination type	Male solder
IP rating	50
AWG wire size	0.00 - 0.00
Cable Ø	3.30 - 4.10 mm
Status	active
Matching parts	ERA.00.250.CTL



Image is for illustrative purpose only

Download

Request a quote Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model	FFA*: Straight plug with oversize cable collet
Keying	Circular, male
Housing Material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces
Weight	5.34 g
Performance	
Configuration	00.250 : 1 Coax (50 Ohm)
Insulator	T: PTFE
Rated Current	4 Amps
Specifications	

Contact Type: Coaxial 50 Ohm (Solder) Contact Dia.: 0.7 mm (0.028in) Bucket Dia.: 0.6 mm (0.024in) Test voltage: 2.1 kV (rms) R (max): 6.1 mOhm Vtest: 2100 V (AC), 3000 V (DC)


Impedance: 50 Ohm

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

Endurance (Shell): 5000 mating cycles F ret (min): 100 N Salt Spray Corrosion: >1000 hr

DRAWINGS



Dimensions

	А	В	L	Μ	S1	S2
mm.	6.4	8	36.5	28.5	7	6.5
in.	0,25	0,31	1,44	1,12	0,28	0,26

RECOMMENDED BY LEMO

Tools

Spanner wrench:

DCD.00.003.PA045

Cables

18000	PTFE	Brown	-10

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

CCX.95.RG1.80BU36M	PTFE	Brown	-12 -12
CCX.95.RG1.95AU37B	PFA	White	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.