



PowerVerter Ultra-Compact Inverter - Portable Power for All Applications

MODEL NUMBER: **PV600**

Description

Harness your vehicle's battery to efficiently power appliances, small electronics and office equipment on the road. Continuously supplies up to 600 watts of 120V AC power to 3 AC outlets from any 12V battery. Ultra-compact, lightweight metal case design is among the smallest, most rugged inverters available.

Features

- Provides 120V AC power for a variety of mobile applications
- 600 watts continuous output power and 1200 watts peak output power (instantaneous)
- 3 AC outlets
- Ultra-compact, extruded aluminum casing stands up to the toughest environments
- Cooling fan lengthens inverter service life
- Integrated mounting feet provide safe, fixed installation
- Low battery alarm/shutdown detects low voltage and shuts down inverter
- Overload alarm/shutdown detects wattage overload on inverter outlets and shuts down inverter as a protective measure
- DC input terminals assure solid connection to battery with user-supplied cables
- Lighted on/off switch shows inverter operations in cramped or dark environments

Highlights

- 600 watt continuous output; 1200 watt peak output (instantaneous)
- Converts 12V DC (battery) power into 110-120V AC (household) power; 3 AC outlets
- Installs in minutes (includes integrated mounting feet)
- Provides a quiet alternative to generator noise and fumes
- Includes "battery saver" low voltage alarm/shutdown

Package Includes

- PV600 Ultra-Compact DC-to-AC Inverter
- Instruction manual

Specifications

OVERVIEW	
UPC Code	037332119889
OUTPUT	
Frequency Compatibility	60 Hz
Output (Watts)	600W (continuous)/1200W (peak)
Output Nominal Voltage	120V
Output Voltage Regulation	Maintains PWM sine wave output voltage of 115 V AC (+/- 8 V AC)
Output Frequency Regulation	60 Hz (+/- 3 Hz)
Overload Protection	Via set of 2 40A automotive input fuses
INPUT	
Recommended Electrical Service	Requires 12V DC input source capable of delivering 64A for the required duration (when used at full capacity). For automotive applications, professional hardwire installation with 80A battery system fusing is recommended.
Maximum Input Amps / Watts	Full continuous load - 64A at 12V DC, No load - 0.95A at 12V DC, Shutdown - 150 microamps
Input Connection Type	Set of 2 DC bolt-down wiring terminals



Input Cord Length Details	User supplies cabling. Minimum gauges for full load operation: 8 (6 ft max), Two 10 (8 ft max), 6 (10 ft max), 4 (15 ft max).
Voltage Compatibility (VDC)	12
BATTERY	
DC System Voltage (VDC)	12
USER INTERFACE, ALERTS & CONTROLS	
Switches	Lighted on/off power switch
Audible Alarm	Dual function alarm indicates overload conditions or low DC input voltage of 10.5V or less.
PHYSICAL	
Cooling Method	Fan
Material of Construction	Aluminum / sheet metal
Shipping Dimensions (hwd / cm)	10.16 x 16.51 x 26.04
Shipping Dimensions (hwd / in.)	4.00 x 6.50 x 10.25
Shipping Weight (kg)	1.36
Shipping Weight (lbs.)	3.00
Unit Dimensions (hwd / cm)	7 x 12.7 x 21
Unit Dimensions (hwd / in.)	2.75 x 5 x 8.25
Unit Weight (kg)	1.13
Unit Weight (lbs.)	2.5
ENVIRONMENTAL	
Relative Humidity	0-95% non-condensing
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>