


SSR21NV-M35047

Aliases (UALM21NV350470)

KEMET, SSR21NV-M/NH-M, AC Line Filters, Common Mode, 4.7 mH



Click here for the 3D model.

Dimensions	
L	22mm MAX
Т	16mm MAX
Н	27mm MAX
LL	3.5mm +/-0.5mm
S	13mm +/-0.5mm
S1	10mm +/-0.5mm
Wire Size	0.6mm

Packaging Specifications	
Packaging	Tray
Component Weight	14.5 g

General Information		
Series	SSR21NV-M/NH-M	
Style	Through-Hole	
Features	High Performance, High Impedance, Strong Inductance	
RoHS	Yes	
Miscellaneous	Temperature Rise Maximum: 55 K.	
Core	Mn-Zn Ferrite	

Specifications	
Voltage AC	250 VAC
Inductance	4.7 mH (10 kHz)
Current	3.5 A
Temperature Range	-25/+120°C
DC Resistance	60 mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.