

## Specification Sheet

Part Number: 181-93010



Wiring Duct Cover for 3" Duct, 6 ft Long, PVC, White, 30ft/box

**Article Number**

181-93010

**Type**

TC3

**Color**

White (WH)

**Features & Benefits**

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
  - Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
  - Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off.
- (Covers to be purchased separately)

**Quantity Per**

box

**Product Description**

HellermannTyton's Pro-Duct wiring duct covers are sold separately and interchangeable among the 3 styles of duct (solid, slotted and high density). Manufactured from high impact, rigid PVC, Pro-Duct covers come in standard colors of white, gray and black. Wiring duct covers are available in 6 foot lengths.

|                                       |  |
|---------------------------------------|--|
| <b>Short Description</b>              | Wiring Duct Cover for 3" Duct, 6 ft Long, PVC, White, 30ft/box |
| <b>Global Part Name</b>               | TC3-PVC-WH   |
| <b>Technical Description</b>          | Wiring Duct Cover for 3" Duct, White                           |
| <b>Length L (Imperial)</b>            | 6.0  |
| <b>Length L (Metric)</b>              | 1.83   |
| <b>Width W (Imperial)</b>             | 3.0  |
| <b>Width W (Metric)</b>               | 76.2   |
| <b>Height H (Imperial)</b>            | 0.308  |
| <b>Height H (Metric)</b>              | 7.82   |
| <b>Material</b>                       | Polyvinylchloride (PVC)  |
| <b>Material Shortcut</b>              | PVC  |
| <b>Flammability</b>                   | Self-Extinguishing   |
| <b>Halogen free</b>                   | No   |
| <b>Operating Temperature (Metric)</b> | +122°F (+50°C)   |
| <b>Reach Complaint(Article 33)</b>    | No   |

|  |  |
|--|--|
| <b>ROHS Complaint</b>                  | Yes  |
| <b>Certification/Specification WEB</b> | EN 50085-1:2005 + A1:2013 CSA UL EN 50085-2-3_1A |
| <b>UL Recognized (US)</b>              | Yes  |
| <b>Package Quantity(Imperial)</b>      | 30   |
| <b>Package Quantity (Metric)</b>       | 9.14   |
| <b>Customs Number</b>                  | 3925900000                                       |