

# KBH22

## Touch Metal Piezo Keypad



## Touch Metal 5x4 Piezo Keypad

### Description

Touch Metal 5x4 Piezo Keypad, front mounted measuring 112X93mm with 4mm mounting holes. Metal housings are machined, one piece construction and 9mm thick with permanently anodized graphics and completely potted. Connection is via flat cable or pins and standard output is matrix or common bus.

### Approvals

- MIL-STD - 810C, 202E, 461B, 462
- CE - EVERSWITCH products comply with Directives
- 2006/95/EEC for low voltage components.
- IP Rating – IP69K Compatible with IEC 60529; EN 60529
- EMC: Directive 2004/108/EWG

### Characteristics

- Function: 20 Momentary keys
- Configuration: Matrix / Common Bus
- Proven reliability: Tested for 50,000,000 cycles
- Weatherproof: For use in harshest outdoor conditions
- Touch Activated: Operable with gloves, tools, etc.
- Sterilizable: Wash down proof up to 100 BAR
- Vandal Resistant: For use in high traffic and abusive areas
- Zero power required for keypad operation
- Eliminates RFI, EMI and ESD issues
- Five year warranty

### Customized Options

A wide range of design options are available: connectors, key function (continuous, toggle, slide types), current rating (up to 10A), graphics, mounting and housing dimensions and materials. We offer RS-232, RS-485, USB and other data outputs. Keypads can be modified to include displays, LEDs, data ports, card readers, cameras, buzzers, etc.

### References

KBH11

## TECHNICAL DATA

### Electrical Data

Key Function	N.O. Momentary
Key Voltage	0-24V AC/DC
Switch Current	0.2A std (0.5A option)
Rated Breaking Capacity	1W
Operating Cycles	>50,000,000
Switch Resistance OFF	> 5 MΩ
Switch Resistance ON	< 20 Ω
Capacity	30 pF

### Mechanical Data

Housing Materials	Aluminum 6061 T651
Housing Method	Machined one piece construction
Actuating Force	3-5 Newton
Connection	Flat cables/pins
Actuating Travel	0.002 mm
Shock Protection	IK 06

### Environmental Data

Operating Temperature	-40 to +125 °C
Storage Temperature	-40 to +125 °C
IP-Protection	IP69K