



General Information		
Series	FX5	
Style	Sheet	
Description	Flex Suppressor High Permeability Type	
Features	High Permeability Type	
RoHS	Yes	
Qualifications	UL94 HB, UL File No. E176124	
Environment	RoHS Compliant, Halogen Free, PVC Free, Lead Free, Red Phosphorus Free	

Specifications			
Temperature Range	-40/+105°C		
Permeability	150 u At 3MHz		
Effective Frequency	1 MHz to 3GHz		
Specific Gravity	3.3 TYP		
Thermal Conductivity	1.1 typical		
Surface Resistivity	1 MOhm/sq. TYP		

Click here for the 3D model.

Dimensions		
Sheet Size	240mmx50M	
L	50000mm NOM	
W	240mm NOM	
Т	0.025mm NOM	

Packaging Specifications	
Tape Description	No Adhesive Tape
Component Weight	990 g

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.