

PARALLEL

Wire combination table for parallel splices specified by UL

AWG#	↓ Number of wires																			
P-1.25																				
22	2	2	2	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
20	1			2	1	1	1	1	1	3	2	2	1	1						
18		1			1			1			1		1		2					
16								1						1						
P-2																				
22	2	2	2	2	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
20	1				2	1	1	1	1				3	2	2	2	1	1	1	1
18		1				1				2	1	1		1			2	1	1	1
16			1				1			1		1		1			1		2	1
P-5.5																				
18	3	2	2	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
16	1	1		1					2	1	1	1								
14					1					1			2							
12						1					1									
10							1					1								
P-8																				
16		1																		
14			1																	
12	2			1																
10		1	1	1																
P-14																				
14		1																		
12			1																	
10	2																			
8		1	1																	
P-22																				
10		1																		
8	2		1																	
6		1	1																	
P-38																				
8		1																		
6	2																			
4		1																		
P-60																				
6		1																		
4	2																			
2		1																		
P-70																				
6		1																		
2	2																			
1/0		1																		
P-80																				
4	1																			
2/0	1																			
P-100																				
2	1																			
2/0	1																			
P-150																				
2		1																		
1/0			1	1																
2/0	2		1																	
3/0		1		1																
P-180																				
1/0		1																		
2/0			1	1																
3/0	2			1																
4/0		1	1																	
P-200																				
2/0			1																	
3/0		1																		
4/0	2	1																		
250/MCM			1																	
P-325																				
4/0	1																			
250/MCM		2																		
300/MCM	1																			

Note: 1) The combinations indicated in the table conform to UL standards only.