

Recommended PCB Layout
(Bottom View)

Materials and Finish

Housing: PBT Thermoplastic
15% Glass Filled, Black Color
UL 94V-0 Rated

Terminals: Copper Alloy
Matte Tin Plating

Barrel: Brass, Nickel Plated

Electrical Characteristics

Rated Voltage:
DC 24 V

Rated Current:
3.0 A

Contact Resistance:
Before Test: 50 milliohms max.
After Durability Test:
100 milliohms max.

Insulation Resistance:
More than 100 Megohms
at 500V DC

Dielectric Strength:
500V AC RMS for 1 minute

Operating Temp:
-40°C to +105°C

Mechanical Characteristics

Insertion Force:
0.3kg - 3.0kg

Extraction Force:
0.3kg - 3.0kg

Durability:
5000 Mating Cycles Min.

Tolerances

X.X ± 0.3
X.XX ± 0.15
Unless Stated
Otherwise


RoHS COMPLIANT

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	6/2/06	Release Drawing	H. MA	N/A	R. Aguirre	07/11/05
A2	6/2/08	Add Nut Info.	S. Vien	H. MA		
B1	08/04/09	ECO #09-045	S. Vien	H. MA		
B2	07/27/11	ECO #11-049	S. Vien	H. MA		
B3	08/14/18	Update Address	D. Shehan	N/A		
B4	04/22/19	ECO #19-035	C. Kelleher	D. Shehan		

STX-3081-3C

Low Profile Stereo Jack, RoHS Compliant

3 Position, Metal Bushing, Threaded Barrel



UNITS
mm