




VMDSC75-55-M12-40-Z

Ruland VMDSC75-55-M12-40-Z, Vibration Isolation Mount, 75mm OD, M12 Threaded Stud, 37mm Stud Lengths, 55mm Height, 40 Shore A Natural Rubber Jacket, Steel



Description

Ruland VMDSC75-55-M12-40-Z is a vibration isolation mount with two threaded studs. It has a 75mm outside diameter, M12 threaded stud, 37mm stud lengths, and 55mm height. This vibration isolation mount is used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. It is often referred to as a sandwich mount or rubber buffer because it functions as shock or vibration isolator sandwiched between two machine components or surfaces. VMDSC75-55-M12-40-Z can be mounted to the system by passing it through an unthreaded hole and securing with a nut or threading it directly into tapped holes on the components it will be mounted to. The rubber jacket is made from natural rubber which has good elasticity and is well suited for most industrial equipment. It has 40 Shore A hardness for high dampening and shock absorption. The zinc plated steel body allows for high strength and is suitable for most industrial applications. VMDSC75-55-M12-40-Z is manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	2.95 in (75 mm)	Height (H1)	2.17 in (55 mm)
Thread (TH)	M12 x 1.75	Plate Thickness (PT)	0.12 in (3 mm)
Stud Length (LS)	1.46 in (37 mm)	Spring Rate	1427.54 lb/in (250 N/mm)
Shore Hardness	40A (+/- 5)	Max Deflection	0.54 in (13.7 mm)
Max Axial Load	780.09 lb (3470 N)	Geometry	Cylindrical
Rubber Material	Natural Rubber	Metal Material	Zinc Plated Steel
Metallic Body Finish	Zinc-Plated	Country of Origin	Hungary
Weight (lbs)	1.026300	UPC	634529356555
Tariff Code	4016.99.6000	UNSPC	31162804
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		