

ISSUE NUMBER

(1)

ORIGINAL

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0, **BLACK IN COLOUR** STEEL, NICKEL PLATED CONTACT: COPPER ALLOY, 30µ GOLD PLATING

OPERATING TEMPERATURE: -55°C ~ 85°C

CURRENT RATING: 3A PER CONTACT CONTACT RESISTANCE: $25m\Omega$ MAX. **INSULATOR RESISTANCE:** 5000MΩ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC rms

		-							
			SW REFERENCE NO.: 663 ASSEMBLY						
663 SERIES D-SUB CONNECTOR		DRAWN: C.B			DATE: AUG. 01/2018				
		CHECKED:			DATE:				
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE:	(IN C.A.D. 1	:1)	SHEET	1	OF	1	
TORONTO, ONTARIO CANADA		DRAWING NUMBER: 663-037-6			664-054			ISSUE	
TION TO QUALITY & SERVICE		PART NUN	/BER:	663-037-6	64-054			1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

