BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape





ATS Part#:

Description:

ATS-52310G-C1-R0

31.00 x 31.00 x 12.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape

Heat Sink Type: maxiFLOW Heat Sink Attachment: **Thermal Tape** Equivalent Part Number: ATS-52310G-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling .
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low .
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks •

Thermal Performance

| AIR VELOCITY | | @200 LFM 1.0 M/S | @300 LFM 1.5 M/S | @400 LFM 2.0 M/S | @500 LFM 2.5 M/S | @600 LFM 3.0 M/S | @700 LFM 3.5 M/S | @800 LFM 4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 4.3 °C/W | 3.5 °C/W | 3 °C/W | 2.7 °C/W | 2.5 °C/W | 2.3 °C/W | 2.2 °C/W |
| | Ducted Flow | 3.5 | N/A | N/A | N/A | N/A | N/A | N/A |

Product Detail

| Schematic Image | Dimension A | Dimension B | Dimension C | Dimension D | ТІМ | Finish |
|--|--|--|---|--|-----------|-----------------------------------|
| | 31.00 mm | 31.00 mm | 12.50 mm | 54.94 mm | T412 | BLUE-ANODIZED |
| | Dimension ATS-5231 (Saint-Gol Thermal p application ATS resen performant ATS certification | 0G-C2-R0 is the exa bain C675). performance data are n. rves the right to upda nce. ies that this heat sin | emponent size. neight from the bottor act heat sink assemb e provided for referer ate or change its proo k assembly is RoHS astom options availab | oly with an equivalen nce only. Actual perfe ducts without notice -6 and REACH comp | t thermal | interface material may vary by |
| *Image above is for illustration purpose only. | | | | | | |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.

