## **HellermannTyton**

## **Specification Sheet**

Part Number: SNP3810H4

Installation and removal can be five times faster than conventional clamps

Heat stabilized material is suitable for high temperature applications.

Completely reusable

Will not rust or corrode

Safety engineered.

No protruding band or cluster.

Can be installed with hose in place

One-hand installation for tight places.

Snapper Hose Clamp, 1.62"-1.89" Bundle Diameter, POM, White, 500/pkg

**Article Number** 

190-00245

Туре

SNP38

Color

White (WH)



| Quantity Per                 | bag   |
|------------------------------|---|
| Product Description          | The Snapper Hose Clamp features a ratchet-style closure for reduced<br>assembly time. It can be added after connection of the hose. Release<br>by sliding the ratchet ends apart. These white polyacetal Snappers<br>can be used in under-hood applications and are stable in a wide<br>variety of chemicals including salts, bases, alcohols, ethers,<br>detergents, gasoline, lubricating oils and greases. Custom design and<br>color options are available based upon application and volume<br>requirements. |
| Short Description            | Snapper Hose Clamp, 1.62"–1.89" Bundle Diameter, POM, White, 500/pkg  |
| Global Part Name             | SNP38-POM-WH  |
| Fixation Method              | Plug-in mounting  |
| Variant                      | Closed  |
| Wall Thickness WT (Imperial) | .068  |
| Wall Thickness WT (Metric)   | 1.7   |
|                              |   |
| Material                     | Polyacetal (POM)  |
| Material Shortcut            | РОМ   |
| Flammability                 | UL 94 HB  |
| UV Resistant (Yes/No)        | No  |

| Operating Temperature       | -40°F to +194°F (-40°C to +90°C) |
|-----------------------------|----------------------------------|
| ROHS Compliant              | Yes                              |
| Package Quantity (Imperial) | 500                              |
| Package Quantity (Metric)   | 500                              |
| Customs Number              | 3926909988                       |

© 2021 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions