

## Specification Sheet

Part Number: 596-00648

Preprinted Solar Labels are made with UV-stable inks and materials for durability, weather resistance and long-term outdoor use. Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.

High abrasion and scuff resistance for high performance labeling.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.



Pre-Printed Header Label, DANGER, 3.0" x 2.0", UV, PET, Red, 250/roll

**Article Number**

596-00648

**Type**

3X2DANGERUV

**Color**

Red (RD)

**Quantity Per**

roll

**Product Description**

These labels come with preprinted color headers so only one color of ribbon is needed to complete the message panel. Labels can be used with TagPrint® Pro label software and HellermannTyton thermal transfer printers to reduce labor, eliminate minimum orders and allow the user to create labels on demand.

**Short Description**

Pre-Printed Header Label, DANGER, 3.0" x 2.0", UV, PET, Red, 250/roll

<b>Global Part Name</b>	3X2DANGERUV-PET-RD
<b>Technical Description</b>	Pre-Printed Header Label, DANGER, 3" X 2", UV, Red
<b>Width W (Imperial)</b>	3.0
<b>Width W (Metric)</b>	76.2
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	2.0
<b>Height H (Metric)</b>	50.8
<b>Width of Liner (Metric)</b>	81.28
<b>Width of Liner (Imperial)</b>	3.2
<b>Material</b>	Polyester (PET)
<b>Material Shortcut</b>	PET
<b>Adhesive</b>	Acrylic
<b>Halogen Free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)

<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	CSA 66956 NEC2014 NEC2011 UL 969 IFC 2012 NEC2017 ANSI Standard Z535.4 NEC2020
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	250
<b>Package Quantity (Metric)</b>	250
<b>Customs Number</b>	3919102055
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1