

Network Surge Suppressor - Essential protection for data and communication lines

MODEL NUMBER: DRS232



Description

Tripp Lite's DRS232 offers dataline surge suppression for the protection of POS equipment, serial printer spoolers, multiplexers and other network devices using RS232 ports running on unshielded twisted pair (UTP). Convenient RJ45 input and output connections with included 5 inch ethernet patch cable allows convenient in-line placement at the protected device network connection. Surge suppression is handled with balanced arrays of high-speed avalanche diodes that divert excess energies created by electrostatic discharges, faulty wiring or lightning away from network interface connections. Tripp Lite network surge suppressors reduce blown interface cards, garbled transmissions, system lock-ups and hard equipment failure by safely shunting dataline surges to ground. Six inch heavy guage grounding lead connects to designated grounding lugs available on the back panel of most network workstations and pieces of internetworking equipment. Lifetime warranty.

SUPPRESSION: 1 set RJ45 in/out jacks, protects wires 1-8, 18V clamping

Features

- DRS232 protects network devices with RS232 ports running on unshielded twisted pair lines
- Convenient RJ45 input and output connections make for simple installation (RJ45 input/output connections, pins 1-8, 18V clamping)
- 5 inch ethernet patch cable enables ideal protection placed as close as possible to the point of use
- Surge suppression utilizing high speed avalanche diodes divert excess energies on the network to ground
- 6 inch heavy gauge grounding lead connects to designated grounding lugs on protected equipment
- Lifetime product warranty

Specifications

OVERVIEW	
UPC Code	037332010827

Highlights

- Complete dataline (RS-232) surge protection
- Protects against the effects of electrostatic discharge, faulty wiring and lightning
- Lifetime product warranty
- Heavy duty grounding lead

Package Includes

- DRS232 dataline protector
- 5-in. RJ45 patch cable
- Instruction manual with warranty information





OUTPUT		
Circuit Breaker (amps)	340	
INPUT		
Recommended Electrical Service	120V, 230V	
Input Plug Type	RJ45	
Input Cord Length (ft.)	0	
Right-Angle Plug	No	
Input Cord Length (m)	0.00	
Integrated Cord Clip	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
SURGE / NOISE SUPPRESSION		
Clamping Voltage (RMS)	18	
Auto Shut-Off	No	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	Yes	
Additional Dataline Protection	1-8	
PHYSICAL		
Anti-Microbial Protected	No	
Integrated Keyhole Mounting Slots	No	
Shipping Dimensions (hwd / cm)	12.70 x 7.62 x 5.08	
Shipping Dimensions (hwd / in.)	5.00 x 3.00 x 2.00	
Shipping Weight (kg)	0.08	
Shipping Weight (lbs.)	0.18	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

https://www.tripplite.com/products/product-certification-agencies