ATGBICS QSFP-4X10G-LR Cisco Compatible Transceiver QSFP+ 40GBase-PLR4 (1310nm, SMF, 10km, MPO, DOM)

Brand : ATGBICS Product code: QSFP-4X10G-LR-C

Product name : QSFP-4X10G-LR Cisco Compatible Transceiver QSFP+ 40GBase-PLR4 (1310nm, SMF, 10km, MPO, DOM)



QSFP-4X10G-LR Cisco Compatible Transceiver QSFP+ 40GBase-PLR4 (1310nm, SMF, 10km, MPO, DOM)

ATGBICS QSFP-4X10G-LR Cisco Compatible Transceiver QSFP+ 40GBase-PLR4 (1310nm, SMF, 10km, MPO, DOM):

ATGBICS QSFP-4X10G-LR 40GBase-PLR4 supports a distance of up to 10km over single mode fibre (SMF) using a wavelength of 1310nm via an MPO connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of QSFP-4X10G-LR= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Features	
SFP transceiver type * Fiber optic Maximum data transfer rate * 40000 Mbit/s Interface type * QSFP+ Single-mode fiber (SMF) supported Multi-mode fiber (MMF) supported Fiber optic connector MPO SFP transceiver standard PLR4	40000 Mbit/s	Certification	CE, FCC, RoHS
		Power	
	∀ ×	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 3.5 W
	ximum transfer distance velength 1310 nm ernet LAN ernet interface type 40 Gigabit Ethernet ital Diagnostics Monitoring M) velength-division multiplexing DM) x tures duct colour Silver using material Silver Metal	Operational conditions	
Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring (DDM) Wavelength-division multiplexing (WDM) Features		Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95% 13.5 mm 72.4 mm
Product colour		Height Weight	18.4 mm 42 g
Plug and Play Hot-Plug support Hot-swap		Packaging data	
	√ √	Number of products included Package type	1 pc(s) Box
Easy to install	√	Technical details	
Country of origin Brand compatibility	United Kingdom Cisco	Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead



5056468716514

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.