

ATGBICS 10GB-BX20-U-C network transceiver module Fiber optic 10000 Mbit/s SFP+

Brand : ATGBICS **Product code:** 10GB-BX20-U-C

Product name: 10GB-BX20-U-C



Extreme Compatible Transceiver, SFP+, 10GBase-BX-U, BiDi, Tx1270nm/Rx1330nm, 10km, SMF, DOM, Ind

ATGBICS 10GB-BX20-U-C network transceiver module Fiber optic 10000 Mbit/s SFP+:

ATGBICS 10GB-BX20-U 1000Base-BX SFP supports a distance of up to 10km over single mode fibre (SMF) using a wavelength of Tx1270nm/Rx1330nm via an LC connector. This bidirectional unit must be used with another transceiver or network appliance of complimenting wavelengths. This product is suitable for rugged environments and can operate at temperatures between -40C to +85C. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Extreme10GB-BX20-U= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Power	
Interface type * SFP+	10000 Mbit/s SFP+	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Tx wavelength (max) Rx wavelength (max)	er optic connector Itransceiver standard It	Operational conditions Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 °C 185 °C -40 - 85 °C -40 - 85 °C 0 - 95% 0 - 95%
Digital Diagnostics Monitoring		Weight & dimensions	
(DDM) Features Product colour		Width Depth Height	13.4 mm 56.5 mm 8.5 mm
Housing material Plug and Play		Weight Packaging data	19 g
Hot-swap Easy to install		Number of products included Package type	1 pc(s) Box
Country of origin United Kingdom Brand compatibility Extreme Networks	United Kingdom Extreme Networks	Technical details Sustainability certificates	RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.